Acoustic Neutrino Detection in Ice

Past, Present and Future

Timo Karg

5th International ARENA Workshop
19 – 22 June 2012 in Erlangen

- > Motivation and Brief History of Acoustic Detection in Ice
- > Generation and Measurement of Sound in Ice
 - Sensor calibration challenge
 - Thermo-acoustic model and its experimental verification
- > Results from Site Exploration
 - SPATS: The South Pole Acoustic Test Setup
- > Future Role of Acoustic Detection (personal view)
- > Conclusions

Acoustic Neutrino Detection...

...in Ice

“Super-Hybrid” Detection of EHE Neutrinos in Ice

Ice allows us to use **three** different techniques:
optical, radio, and acoustic

“Super-Hybrid” Detection of EHE Neutrinos in Ice

Ice allows us to use **three** different techniques:
optical, radio, and acoustic

“Super-Hybrid” Detection of EHE Neutrinos in Ice

Ice allows us to use **three** different techniques:
optical, radio, and acoustic

First Ideas: Theoretical Considerations

- > P. B. Price, Nucl. Instrum. Meth. A **325** (1993) 346:
Mechanisms of attenuation of acoustic waves in antarctic ice
“The results of this study indicate that it would be worthwhile to investigate acoustic detection further. The next set of experiments by the AMANDA collaboration at the South Pole will include an investigation of noise, sensitivity, and attenuation using acoustic generators and detectors at depths of ~ 1 km.”
- > P. B. Price, Astropart. Phys. **5** (1996) 43:
Comparison of optical, radio, and acoustical detectors for ultra-high energy neutrinos
“The acoustical technique is least sensitive, the mechanism of energy conversion from a cascade to an acoustic signal is very inefficient, and no tests have been carried out with particle beams.”
- > P. B. Price, J. Geophys. Res. **111** (2006) B02201:
Attenuation of acoustic waves in glacial ice and salt domes
“At frequencies relevant to future searches for hydrodynamic waves emitted in ultrahigh-energy neutrino-induced cascades (~ 10 to ~ 60 kHz), both glacial ice and salt domes look promising.”

Acoustic R&D in IceCube

2002

start

2003

development of
glaciophones

test in lab and at
accelerators

Improvement
 $(S/N)_{ib} = 50$
 $(S/N)_{gb} = 15$

2004

hybrid detector simulation

2005

calibration of
sensors and
transmitters

construction
and test of
SPATS

2006

First SPATS deployment

In-situ test starts

First SPATS results

Slide courtesy of R. Nahnauer

In 2002: Sensor Development and Sound Generation

> Ice

- $130 \times 54 \times 25 \text{ cm}^3$

> Detector

- 13 inch glass sphere
- piezo elements pressed at arbitrary positions to sphere

> Thermo-acoustic sound generation via laser

- wave length: 1056 nm
- pulse: 6 ns $\times$ 1 Hz
- energy: $\sim 10 \text{ mJ / pulse}$
 $\sim 6 \times 10^{16} \text{ eV}$

ink used
as absorber
for laser

First Ideas: Detector Simulations

> IceCube extension (100 km³)

- 13 optical strings ($r = 1$ km)
- 91 radio / acoustic strings (1500 m deep)
 - 5 radio receivers / string
 - 300 acoustic receivers / string

> Assumptions

- acoustic trigger threshold: 9 mPa in ≥ 3 sensors
- depth dependent acoustic attenuation length (P. B. Price, J. Geophys. Res. **111** (2006) B02201):
 - 8.6 km @ surface
 - 0.7 km @ 2000 m depth

> Results

- acoustic: 16 GZK neutrino events / year
- radio: 12 GZK neutrino events / year
- in coincidence: 8 GZK neutrino events / year

Sound in Ice

Generation and Measurement

Sound in Ice

~~Generation and Measurement~~
Measurement and Generation

The Little Difference Between Water and Ice

> Water

- shear modulus $G = 0$
- pressure waves only

> Ice

- pressure and shear waves possible
- P- and S-waves have different velocities
- S-waves make problem more complex
- S-waves carry additional information

Image:

<http://www.astro.uwo.ca/~jlandstr/planets/webfigs/earth/images/waves.gif>

P - wave

S - wave

Measurement Principle: Piezoelectric Effect

- > **Piezoelectricity** is the charge that accumulates in certain solid materials in response to applied mechanical stress.
- > Very simplistic view:
Force along one crystal axis

$$Q = \varepsilon_{33} d_{33} F$$

Image: Mael Guennou - Titzeff
via Wikimedia Commons

Measurement Principle: Piezoelectric Effect

> **Piezoelectricity** is the charge that accumulates in certain solid materials in response to applied mechanical stress.

> Very simplistic view:
Force along one crystal axis

$$Q = \varepsilon_{33} d_{33} F$$

> More complex view:

$$\partial_k (c_{iklm} S_{lm} + e_{lik} E_l) = \rho \ddot{u}_i$$

$$\partial_i (e_{ilm} S_{lm} + \varepsilon_{il} E_l) = 0$$

Image: Mael Guennou - Titzeff
via Wikimedia Commons

Measurement Principle: Piezoelectric Effect

> **Piezoelectricity** is the charge that accumulates in certain solid materials in response to applied mechanical stress.

> Very simplistic view:
Force along one crystal axis

$$Q = \varepsilon_{33} d_{33} F$$

> More complex view:

$$\partial_k (c_{iklm} S_{lm} + e_{lik} E_l) = \rho \ddot{u}_i$$

$$\partial_i (e_{ilm} S_{lm} + \varepsilon_{il} E_l) = 0$$

> Even worse:

The material “constants” are not constant

$$c_{iklm} = c_{iklm}(p_{\text{stat}}, T) \quad \text{elasticity tensor}$$

$$e_{ikl} = e_{ikl}(p_{\text{stat}}, T) \quad \text{piezoelectric tensor}$$

$$\varepsilon_{ik} = \varepsilon_{ik}(p_{\text{stat}}, T) \quad \text{permittivity tensor}$$

Image: Mael Guennou - Titzeff
via Wikimedia Commons

Sensor Calibration: The Challenge

- > Calibration in water well understood:
e.g. SPATS sensors calibrated in water at 0°C prior to deployment
(relative to a reference hydrophone)
- > Environmental conditions in ice completely different:
e.g. South Pole
 - Temperature -50°C
 - Increased static ambient pressure (varies with depth)
 - Different coupling from medium to sensor (acoustic impedance)
- > Cold ice at high pressure hard to reproduce in the lab
 - Possibility: Study different effects separately

Sensitivity vs. Temperature

- > Sensor cooled down in air
- > Keep transmitter at room temperature
 - avoid changes in emission due to varying temperature!
- > Sensitivity increases by a factor of 1.45 ± 0.15 going from 0 to -50°C

Sensitivity vs. Pressure

- Sensor in water in pressure vessel
- Keep transmitter at normal pressure
 - avoid changes in emission due to varying pressure!
- Sensitivity constant within uncertainties (30%) from 0 to 50 bar

Sensitivity in Water and Ice: Reciprocity Calibration

The chicken-egg-problem...

- No reference receiver for relative calibration available for ice
- Assume reciprocity:
 - sensitivity M is proportional to emissivity S : $M = J \times S$
 - J independent of receiver (but depends on medium and setup geometry)
- Systematic uncertainties in calibration method: 19%

Sensitivity in Water and Ice: Results

- Aachen Acoustic Laboratory allows for acoustic measurements in 3 m³ of clear ice
- Reciprocity calibration of same sensor in water and ice
- Results compatible with constant sensitivity in relevant frequency range

see also:
D. Heinen,
tomorrow morning

Sensor Calibration: What We Do and Don't Know

> We know

- how to calibrate a sensor in water
- sensitivity increases by a factor of 1.5 from 0 to -50°C (for the sensor studied)
- sensitivity is independent of static pressure (within 30% uncertainty)
- sensitivity does not change between water and ice (uncertainty t.b.d.)

> We don't know

- if the three effects are uncorrelated
(if they are, we can determine the in-situ sensitivity)
- if the directional characteristics of the sensor change
(in ice, we can only probe a limited number of directions)

> We have ideas how this can be improved

- in the lab: use thermo-acoustic sound source of known emission strength (laser, particle beam)
- in-situ: place transmitter inside sensor housing, unaffected by environment
(test setup deployed by IceCube collaboration, data under study)

Thermo-acoustic Model

$$\frac{1}{c_s^2} \frac{\partial^2 p}{\partial t^2} - \Delta p = \frac{\alpha}{C_p} \frac{\partial^2 \epsilon}{\partial t^2}$$

$$p(\vec{r}, t) = \frac{\alpha}{4\pi C_p} \int \frac{dV'}{|\vec{r} - \vec{r}'|} \frac{\partial^2}{\partial t^2} \epsilon \left(\vec{r}', t - \frac{|\vec{r} - \vec{r}'|}{c_s} \right)$$

$$\xrightarrow{\text{assume instantaneous energy deposition}} = \underbrace{\frac{\alpha}{4\pi C_p} c_s^2}_{\text{dimensionless factor: medium elastic and thermal properties}} \frac{\partial}{\partial R} \int_{S_r^R} \frac{d\sigma}{R} \tilde{\epsilon}(\vec{r}')$$

Deposited energy density

$\frac{\alpha}{C_p} c_s^2 = \begin{cases} 0.15 & \text{(sea water)} \\ 1.12 & \text{(cold ice)} \end{cases}$

- > Acoustic signal depends on energy density deposited in the medium
- > Model can be tested with artificial energy sources (particle beam, laser)
- > For neutrino detection:
additional uncertainties from hadronic cascade development

Expected Signal Pattern

F. Descamps, PhD thesis,
Universiteit Gent (2009)

J. Vandenbroucke, PhD thesis,
University of California, Berkeley (2009)

- Bipolar pulse in time domain, “pancake” in space
- Signal strongly depends on hadronic model
- For same model, signal in ice stronger by factor of about 7.5 than in water
 - due to medium elastic and thermal properties
- At $E_v = 10^{18} \text{ eV}$ attenuation dominated by geometric $1/r$ factor

Experimental Verification: Particle Induced in Ice

> TSL, University of Uppsala, Sweden

- Cyclotron
- Protons ($E_{\text{max}} = 177 \text{ MeV}$)
- Heavy ions ($E_{\text{max}} / A = 45 \text{ MeV}$)
- Materials science, DNA studies, med. particle therapy

> Available parameter space

- Proton energy: 177 MeV
- Bunch length: $\approx 30 \mu\text{s}$
- Bunch energy: $10^{15} - 10^{18} \text{ eV}$
- Beam diameter: 0.6 – 2 cm
- Ice volume: $130 \times 40 \times 27 \text{ cm}^3$

> Results

- Strong evidence for thermo-acoustic signals
- Signal dominated by reflections
 - quantitative analysis difficult

Experimental Verification: Particle Induced in Water

> Setup

- Same proton beam; hydrophone pos.: 10 – 110 cm
- Temperature: 1.7 – 15°C

> Results

- agreement simulation $\leftrightarrow$ measurement to ~30%
- Signal vanishes around 4°C
- Expected for thermo-acoustic mechanism
 $\alpha(4^\circ\text{C}) = 0$

Experimental Verification: Laser Induced

> Nd:YAG laser

- 1064 nm, 50 mJ (3×10^{17} eV) / pulse, 4 ns pulse length, 3 mm beam diameter

> Installation and handling easier than proton beam

> Clear, reproducible signals

> Once energy deposition profile well understood:

- Good source for absolute sensor calibration!

see also:
D. Heinen,
tomorrow morning

Site Exploration

Questions: Ice Acoustic Properties (10 – 100 kHz)

Get realistic sensitivity estimate for an acoustic neutrino telescope in ice

> Speed of sound and its variation with depth

- significant refraction would make vertex reconstruction difficult

> Attenuation length

- determines sensor spacing / effective volume of neutrino detector
- frequency dependence allows to determine attenuation mechanism

> Noise floor

- determines energy threshold

> Transient noise sources

- impulsive noise must be separated from neutrino signal

requires time information

requires amplitude information

requires amplitude information

requires time information

South Pole Acoustic Test Setup (SPATS)

- > 4 strings in IceCube drill holes
- > instrumented depth: 80 m – 500 m
- > per string:
 - 7 sensors
 - 7 transmitters
- > String-PC
 - digitization
 - time stamping
 - monitoring (p, T)
- > Master-PC
 - data storage
 - GPS clock
 - data transfer via satellite

SPATS Stage Design

Transmitter:

- ring shaped piezo ceramic coated in resin
- HV generator

Sensor:

- 3 channels / sensor
- pre-amplifier
- analogue signal transmission
- steel pressure housing

String-D:

- improved sensors: mechanical decoupling of sensor channels
- improved transmitters: higher power
- HADES: alternative sensor design with piezo ceramics outside the steel housing

© IceCube Collaboration

Extended Range: The Retrievable Finger

➤ Use newly drilled IceCube holes to lower retrievable transmitter

- increased distance range for attenuation length measurements
- sound speed depth profile
- relative sensor calibration

Sound Speed Depth Profile

- First in-situ measurement for P and S waves
- Better than 1% accuracy
- If measurable S waves generated in neutrino interactions: independent distance estimator!

Attenuation Length

> 48 independent measurements

- one for each sensor channel; pinger at different distances
- eliminates uncertainty from sensor calibration

> Weighted mean value and width of distribution:

- $\alpha = 3.20 \pm 0.57 \text{ km}^{-1} \leftrightarrow$
 $\lambda = 312 \text{ m}^{+68 \text{ m}}_{-47 \text{ m}}$

- Independent of depth

> Surprisingly short

- what is the attenuation mechanism?
 - absorption: freq. independent
 - scattering: $\alpha \propto f^4$

> No show stopper

- 1/r attenuation dominant for most energies

Attenuation Length: Frequency Dependence

- Data from multi-frequency pinger: pulses @ 30, 45, and 60 kHz
 - signal at 60 kHz weak; signal extraction under study
- No (or very weak) frequency dependence: certainly not f^4
- Attenuation seems not to be dominated by scattering

Y. Abdou for the IceCube Collaboration, 32nd ICRC, Beijing, August 2011

Noise: Properties and Temporal Evolution

- Gaussian and stable over long time
- Peaks correlated with IceCube drilling, inter-string data taking
- Hypothesis: freeze-in improves coupling to ice causing noise level to increase and then stabilize in the first couple months

Estimation of Absolute Noise Level (10 – 50 kHz)

- Sensitivity correction factor of 1.5 (from temperature)
- Noise level 14 mPa in deep ice (estimated; main uncertainty is sensitivity)
- 14 mPa $\cong$ 10 EeV neutrino interacting in 1000 m distance
 - using (conservative) model of Bevan et al.

Spatial and Temporal Distribution of Transient Events

- Two years of transient data analyzed
 - 4 years available in total
- Refreezing of close IceCube holes and Rod-wells are main (only) sources
- Transient events can be used for in-situ directional calibration!

see also: R. Nahnauer,
tomorrow morning

Upper Limit on Neutrino Flux

- Simulate ν interactions outside IceCube volume and below 200 m (no refraction)
- Trigger threshold 70 mPa (estimated)
- Very promising result for a test setup

What's next?

personal view (might be biased...)

Implications for Acoustic Neutrino Detection

- > Energy threshold for acoustic-only detection expected ≈ 10 EeV
 - rather high, but hasn't changed much since very first (B.S., before SPATS) simulations
- > Acoustic can add valuable additional information in hybrid neutrino detector (e.g. in combination with radio)
 - reduce systematic uncertainties
 - increase confidence in signal in absence of calibration beam (e.g. atmospheric muons / neutrinos in optical neutrino telescopes)
- > Possible scenario:
 - at “low” energies:
use radio for triggering – signal in single acoustic sensor can be significant
 - at “high” energies:
separate acoustic trigger – use hybrid information for direction/energy reconstruction

Possible Radio/Acoustic Hybrid Scenario

K. Hanson, P. Sandstrom (2009): SATRA – Sensor Array for Transient Radio Astrophysics

400 km² array, 3600 holes
acoustic sensor spacing $\Delta x = \Delta y = 333$ m, $\Delta z = 10$ m

	coinc. events/year (ESS-2008)		
acoustic sensor depth	200-400 m	200-600 m	200-1000 m
Vall flavour	27	40	61

signal model: Askaryan

trigger threshold: 10 mPa

trigger condition:

acoustic: ≥ 1 hit

radio: ≥ 6 hits on 3 strings

Sites

http://photolibrary.usap.gov/AntarcticaLibrary/POLE_AERIAL_2.3.11_D.JPG

South Pole

http://upload.wikimedia.org/wikipedia/commons/1/1a/Ross_Ice_Shelf_1997.jpg

Ross Shelf

Concordia Station

http://www.phys.unsw.edu.au/nature/antarctica_map2.gif

<http://upload.wikimedia.org/wikipedia/commons/b/b7/ConcordiaFromTower.jpg>

An Interesting Alternative Site: Permafrost

> Advantages

- large and deep permafrost layers available in nature
- density is ~2 times that of water and ice
- drilling experience from gas and oil companies
- deployment may be easy (freeze-in of detectors)

> Disadvantages

- homogeneity of permafrost in larger depth requires further studies
- no in-situ attenuation measurements for radio and acoustic signals available for interesting locations
- bad infrastructure in most of the deep permafrost regions

Technical Challenges: Deployment

> New deployment techniques required

- many holes at large distances
- but much smaller diameter than IceCube

> Interesting development: IceMole

- Combined drilling and melting probe
- from Aachen University of Applied Sciences, Institute of Aerospace Engineering
- Cabling and sensors stored and deployed from device:
 - holes can re-freeze immediately
 - device can remain in ice after deployment

see also:
R. Hoffmann,
this session

Image: K. Laihem Nucl. Instrum. Meth. A, in press

Summary and Conclusions

- > Ice offers the unique possibility to combine optical, radio, and acoustic detection techniques for EHE neutrinos
- > Generation and measurement of thermo-acoustic signals in the lab well understood
 - Considerable progress in sensor calibration problems!
- > Acoustic ice properties at South Pole studied in detail with SPATS
 - no refraction below 200 m
 - attenuation length 300 m
 - estimated noise level 14 mPa, no deep transient noise outside IceCube volume
- > Results show that acoustic will be a valuable extension to a future EHE neutrino detector
- > New sensor types and deployment techniques under study
- > Just need to start a new project!

Backup Slides

The “Multi-frequency” Pinger

> Frequency dependence of attenuation length $\Rightarrow$ attenuation mechanism

- Absorption: frequency independent; Scattering: $\alpha_{\text{att}} \propto f^4$

> Deep stops (up to 1000 m) to measure sound speed and attenuation in deep ice and on inclined paths

- Also interesting for Glaciology (ice crystal orientation)

Acoustic Addition to ARA?

- String spacing (2 km) on the very large side for acoustic
- Hole depth (200 m) on the shallow side for acoustic
- Geometry unfavorable to an acoustic addition