

Polarimetry at the ILC

Robert Karl ^{1,2} Jenny List ²

¹Deutsches Elektronen-Synchrotron (DESY)

²University of Hamburg

21.11.2016



Universität Hamburg
DER FORSCHUNG | DER LEHRE | DER BILDUNG



PIER
Helmholtz
Graduate
School
A Graduate Education Program
of Universität Hamburg
in Cooperation with DESY



Outline

Introduction

Polarization Measurement using Collision Data

- Comparison of the Statistical Precision for Different Methods

- Impact of Systematic Uncertainties and their Correlations

Improvement by Constraints from Polarimeter Measurement

Summary



Advantages of Polarized Beams

▶ International Linear Collider (ILC)

- ▶ e^-e^+ collider with polarized beams of $|80\%|$ and $|30\% - 60\%|$, respectively
- ▶ Selectable polarization sign $\rightarrow$ choice of spin configuration


▶ Advantages:

- ▶ Sensitive to new observables (e.g. left-right-asymmetry)
- ▶ Reduction of background processes and simultaneously increase of signal processes
- ▶ Deep insights into the chiral structure of the weak-interaction for known and unknown particle

All event rates depend linearly on the polarization!
 $\Rightarrow$ Has to be known as precisely as the luminosity!



ILC Polarimetry Concept



1. Measurement of the time-resolved beam polarization before and after the e^-e^+ IP

- ▶ Via laser-Compton polarimeter

Ref.: Jenny List, Annika Vauth, and Benedikt Vormwald:

A Quartz Cherenkov Detector for Compton-Polarimetry at Future e^+e^- Colliders (<https://bib-pubdb1.desy.de/record/221054>)

A Calibration System for Compton Polarimetry at e^+e^- Colliders (<https://bib-pubdb1.desy.de/record/289026>)

2. Extrapolating the beam polarization to the e^-e^+ IP

- ▶ Via Spin Tracking

Ref.: Moritz Beckmann, Jenny List, Annika Vauth, and Benedikt Vormwald:

Spin transport and polarimetry in the beam delivery system of the international linear collider

(<http://iopscience.iop.org/article/10.1088/1748-0221/9/07/P07003/pdf>)

3. Determination of the luminosity-weighted averaged polarization from collision data

- ▶ Calculating the polarization from known standard model processes

⇒ Discussed in the following

Determination of the Polarization from Collision Data

Goal:

General strategy for the polarization determination which yields the best precision per measurement time

► Previous Work:

- Using the information from W -pair production

Ref.: Theses Ivan Marchesini

(<http://pubdb.xfel.eu/record/94888>)

- Using the information from single W , γ , Z events

Ref.: Talk Graham W. Wilson

(<https://agenda.linearcollider.org/event/5468/contributions/24027/>)

► Current Work:

- Combining all relevant processes, including all uncertainties and their correlations
- Compensating for a non-perfect helicity reversal
- Including constraints from the polarimeter measurement



Introduction

Polarization Measurement using Collision Data

Comparison of the Statistical Precision for Different Methods

Impact of Systematic Uncertainties and their Correlations

Improvement by Constraints from Polarimeter Measurement


Summary



Concept


Example Processes:

W-pair production:



$$\sigma_{LL} = \sigma_{RR} = \sigma_{RL} = 0$$

s-channel spin-1 particle:



$$\sigma_{LL} = \sigma_{RR} = 0$$

- ▶ Calculation of the P from polarized σ measurement of well known SM-process
 - Using the information of their chiral structure
 - ▶ Requirement to consider a process:
 - ▶ Theoretical very well known
 - Reduction of theoretical uncertainties
 - ▶ High absolute cross section (high rate)
 - Minimizing the statistical error
 - ▶ Large left-right-asymmetry
 - Minimizing the influence of systematic uncertainties
 - ▶ Well separable from possible BSM-effects
 - ▶ Feature of the ILC:
 - Using 4 different polarization configuration (→ signs of the polarizations)
- ⇒ Task: Providing the absolute scale calibration

Special Case: The Modified Blondel Scheme (MBS)

► Constraints for the Modified Blondel Scheme:

- Process must fulfill: $\sigma_{LL} \equiv \sigma_{RR} \equiv 0$
- Perfect helicity reversal: $+|P| \longleftrightarrow -|P| \Rightarrow |P| \equiv \text{const.}$

► Unique solution:

4 possible cross section measurements: $\sigma_{-+}, \sigma_{+-}, \sigma_{--}, \sigma_{++}$

Maximal 4 unknown quantities: $\sigma_{LR}, \sigma_{RL}, |P_{e-}|, |P_{e+}|$

► Solve for $|P_{e\mp}|$:

$$\sigma_{\pm\pm} = \frac{(1\pm|P_{e-}|)}{2} \frac{(1\mp|P_{e+}|)}{2} \cdot \sigma_{RL} + \frac{(1\mp|P_{e-}|)}{2} \frac{(1\pm|P_{e+}|)}{2} \cdot \sigma_{LR}$$

► Modified Blondel-Scheme:

$$|P_{e\mp}| = \sqrt{\frac{(\sigma_{-+} + \sigma_{+-} - \sigma_{--} - \sigma_{++})(\pm\sigma_{-+} \mp \sigma_{+-} + \sigma_{--} - \sigma_{++})}{(\sigma_{-+} + \sigma_{+-} + \sigma_{--} + \sigma_{++})(\pm\sigma_{-+} \mp \sigma_{+-} - \sigma_{--} + \sigma_{++})}}$$

► Uncertainties are calculated via analytic error propagation



The Unified Approach: χ^2 -Method

- ▶ Desire for a more general approach:
 - ▶ Consider any process with a polarization dependence + using several processes at once
 - ▶ Compensate non-perfect helicity reversal: $+ |P^R| \longleftrightarrow - |P^L|$

- ▶ Consider a χ^2 -Method: Using all 4 chiral cross sections

$$\chi^2 = \sum_{\text{process}} \left\{ \sum_{\pm\pm} \left[\frac{(\sigma^{\text{data}} - \sigma^{\text{theory}})^2}{\Delta\sigma^2} \right] \right\}$$

- ▶ Compensate non-perfect helicity reversal: 4 free parameters

$$\underbrace{P_L^- = -80\%}_{\text{left-handed } e^- \text{-beam}}$$

$$\underbrace{P_R^- = 80\%}_{\text{right-handed } e^- \text{-beam}}$$

$$\underbrace{P_L^+ = -30\%}_{\text{left-handed } e^+ \text{-beam}}$$

$$\underbrace{P_R^+ = 30\%}_{\text{right-handed } e^+ \text{-beam}}$$

- ▶ Error determination via toy experiments

Introduction

Polarization Measurement using Collision Data

Comparison of the Statistical Precision for Different Methods

Impact of Systematic Uncertainties and their Correlations

Improvement by Constraints from Polarimeter Measurement

Summary



Comparison to the Previous W-Pair Study

Study by Ivan Marchesini:



- ▶ Using $e^-e^+ \rightarrow W^+W^- \rightarrow q\bar{q}l\nu$
- ▶ Statistical uncertainties only
- ▶ Consider equal absolute polarizations (MBS)
- ▶ Including full background study

Adjustment of the current study:

- ▶ Limited to $e^-e^+ \rightarrow W^+W^- \rightarrow q\bar{q}l\nu$
- ▶ Forced equal absolute polarizations ($|P^L| \equiv |P^R|$)
- ▶ Including same background estimation and selection efficiency

Comparison:

- ⇒ χ^2 -method yields better precision under same conditions than the MBS



Comparison to Previous Single $W^\pm, \gamma, Z$ Study

Study by Graham W. Wilson

- Using 4 Processes simultaneously:

$$e^- e^+ \rightarrow \nu \bar{\nu} \gamma; \quad e^- e^+ \rightarrow \nu \bar{\nu} Z$$

$$e^- e^+ \rightarrow e^+ \nu W^- \rightarrow e^+ \nu \mu^- \bar{\nu}$$

$$e^- e^+ \rightarrow e^- \bar{\nu} W^+ \rightarrow e^- \bar{\nu} \mu^+ \nu$$

- Consider equal absolute polarizations

2 Parameters: P_{e-}, P_{e+}

- Consider deviations: 4 Parameters

$$P_{e\pm}^L = -|P_{e\pm}| + \frac{1}{2}\delta_\pm$$

$$P_{e\pm}^R = |P_{e\pm}| + \frac{1}{2}\delta_\pm$$

Comparison to Current analysis

- Differences:

Previous: Constraint on δ : $\Delta\delta < 10^{-3}$

Current: direct fit of $P_{e\pm}^{L,R}$

parameters		$\Delta P/P, \mathcal{L} = 2ab^{-1}$	
#	P	Previous	Current
2	P_{e-}	0.07%	0.051%
	P_{e+}	0.22%	0.21%
4	P_{e-}	0.085%	0.088%
	δ_{e-}	0.12%	0.19%
	P_{e+}	0.22%	0.23%
	δ_{e+}	0.32%	0.56%

$\mathcal{L}$ equally distributed between $\sigma_{\pm\pm}$

Statistical precision only


- Very similar precision even without additional constraint on δ



Combining W-Pair + Single W, Z, γ

Combined vs. W-Pairs alone

- ▶ W-Pair yields only enough information for 2 parameter fit P_{e-}, P_{e+}
 - ▶ Large improvement
→ due to additional processes
 - ▶ Combined: fit of 4 parameters is possible $P_{e-}^L, P_{e-}^R, P_{e+}^L, P_{e+}^R$
- ⇒ Compensation for a non-perfect helicity reversal



Combined vs. Single Boson

- ▶ The 4 processes Single $W^\pm$, Single Z , Single γ yields a large analysis power
- ▶ Combined precision dominated by single boson processes

	single W, Z, γ	Combined
P_{e-}	0.088%	0.079%
δ_{e-}	0.19%	0.18%
P_{e+}	0.23%	0.16%
δ_{e+}	0.56%	0.51%

Introduction

Polarization Measurement using Collision Data

Comparison of the Statistical Precision for Different Methods

Impact of Systematic Uncertainties and their Correlations


Improvement by Constraints from Polarimeter Measurement

Summary



Systematic Uncertainties and their Correlations

Systematic quantity	related to:	
Integrated luminosity	$\mathcal{L}$	accelerator
Selection efficiency	ε	detector
Background estimate	B	theory



Remark:

A non-perfect helicity reversal has close to no influence on the precision due to compensation of the unified approach

► Uncertainties influenced by

- Detector calibration and alignment
- Machine performance
- etc.

⇒ $\Delta\mathcal{L}$, $\Delta\varepsilon$ are time dependent

► Correlations:

- Data sets taken concurrently
 - Generate correlations
- ⇒ Lead to cancellation of systematic uncertainties

⇒ Fast helicity reversal

- Fast switch between $\sigma_{\pm\pm}$ measurements e.g. train-by-train
- ⇒ Faster than changes in calibrations, alignments, etc.

Introduction


Polarization Measurement using Collision Data

Improvement by Constraints from Polarimeter Measurement

Summary



Consider Polarimeter Information



Simplified approach: (as a first step)

- ▶ Assume polarimeter measure directly at IP (neglect spin transport)
- ▶ Use nominal polarimeter uncertainty $\Delta P/P = 0.25\%$:
- ▶ Toy polarimeter measurement:

Gaus-smeared


- ▶ Mean: $P_{e^-} = 80\%$, $P_{e^+} = 30\%$
- ▶ Width: ΔP

Implementation

$$\chi^2 = \sum_P \left[\frac{(P_{e^\pm}^{L,R} - \mathcal{P}_{e^\pm}^{L,R})^2}{\Delta \mathcal{P}^2} \right]$$

- ▶ $P_{e^\pm}^{L,R}$: 4 fitted Parameter
- ▶ $\mathcal{P}_{e^\pm}^{L,R}$: Polarimeter measurement
- ▶ $\Delta \mathcal{P}$: Polarimeter uncertainty

Impact of the Polarimeter Constraint



For idealized situation:

- ▶ Better polarization precision, especially for lower integrated luminosities
- ▶ More robust against large Poisson fluctuations in the cross section measurement

Next step: add more realism

- ▶ Spin tracking including misalignments in the BDS
- ▶ Include impact of collision effect
- ▶ Use upstream and downstream polarimeter separately

Summary

- ▶ Polarization provides a deep insight in the chiral structure of the standard model and beyond
 - ⇒ A permille-level precision of the luminosity-weighted average polarization at the IP is required
- ▶ New unified approach combining all suitable cross sections and the polarimeter measurement
 - ⇒ Higher analysis power by considering various processes
 - ⇒ Further improvement of precision due to polarimeter constraint
- ▶ Unified approach also compensates a non-perfect helicity reversal due to direct fit of:

$$P_{e-}^L, \quad P_{e-}^R, \quad P_{e+}^L, \quad P_{e+}^R$$

- ▶ A fast helicity reversal improves the polarization precision due to cancellation of systematic uncertainties




Backup Slides



Polarization at a e^-e^+ Collider

- ▶ Helicity is the projection of the spin vector on the direction of motion
- ▶ In case of massless particles, helicity is equal to chirality
- ▶ If $E_{\text{kin}} \gg E_0 \longrightarrow m_e \approx 0$



- ▶ For a bunch of particles the polarization is defined as:

$$P := \frac{N_R - N_L}{N_R + N_L}$$



Laser-Compton Polarimeters


Spin Tracking

Collision Data



Laser-Compton Polarimeters


Magnetic chicane of the upstream polarimeters



- ▶ Compton scattering of the beam with a polarized Laser
- ▶ $\mathcal{O}(10^3)$ particles per bunch ($2 \cdot 10^{10}$) are scattered
- ▶ Magnetic chicane: energy spectrum
⇒ spatial distribution

- ▶ Energy spectrum measurement:
⇒ Counting the scattered particles at different positions
- ▶ Design of the magnetic Chicane:
 - ▶ Laser-bunch interaction point moves with beam energy
→ position of the Compton edge stays the same
 - ▶ Orbit of the non-scattered particles is unaffected by the magnetic chicane

Differential Compton Cross Section



Energy dependence:

$$\frac{d\sigma_C}{dy_C} = \frac{2\pi r_e^2}{x_C} (a_C + \lambda \mathcal{P} \cdot b_C); \quad y_C := 1 - \frac{E'}{E}$$

e^- Polarization: $\mathcal{P}$; Laser Polarization: λ

DarkBlue: $\lambda \mathcal{P} = +1$

Cyan: $\lambda \mathcal{P} = -1$

Calculating $\mathcal{P}_i$ of the i -th channel with asymmetry A_i , analysing power Π_i

$$A_i := \frac{N_i^- - N_i^+}{N_i^- + N_i^+}; \quad \Pi_i = \frac{\mathcal{I}_i^- - \mathcal{I}_i^+}{\mathcal{I}_i^- + \mathcal{I}_i^+}; \quad \mathcal{I}_i^\pm := \int_{E_i - \Delta/2}^{E_i + \Delta/2} \frac{d\sigma_C}{dy_C} \Big|_{\lambda \mathcal{P} = \pm 1} dy_C$$

$N_i^\pm := \#e_{\text{Compton}}$ for $\lambda \mathcal{P} = \pm 1$; E_i : energy of i -th channel; Δ : energy width

$$\Rightarrow \lambda \mathcal{P}_i = \frac{A_i}{\Pi_i} \quad \Rightarrow \quad \mathcal{P} = \langle \mathcal{P}_i \rangle$$



Laser-Compton Polarimeters

Spin Tracking

Collision Data



Spin Precession



- ▶ Polarimeters are 1.65 km and 150 m away from IP
 - Particles propagate through magnets
 - Magnets influence the spin, as well
 - Described by Thomas precession

- ▶ if $\vec{B}_{\parallel} = \vec{E} = 0$:

$$\frac{d}{dt} \vec{S} = -\frac{q}{m\gamma} \left((1 + a\gamma) \vec{B}_{\perp} \right) \times \vec{S}$$

- ▶ Effects from focusing and defocusing can cancel
- ▶ For a series of quadrupole magnets $\mathcal{P}$ described by the angular divergence θ_r

$$f(\theta_r) = |\vec{\mathcal{P}}|_{\max} \cdot \cos((1 + a\gamma) \cdot \theta_r)$$

Systematic Polarization Uncertainty

contribution	uncertainty [10^{-3}]
Beam and polarization alignment at polarimeters and IP ($\Delta\vartheta_{\text{bunch}} = 50 \mu\text{rad}$, $\Delta\vartheta_{\text{pol}} = 25 \text{ mrad}$)	0.72
Variation in beam parameters (10 % in the emittances)	0.03
Bunch rotation to compensate the beam crossing angle	< 0.01
Longitudinal precession in detector magnets	0.01
Emission of synchrotron radiation	0.005
Misalignments (10μ) without collision effects	0.43
Total (quadratic sum)	0.85
Collision effects in absence of misalignments	< 2.2

[Ref.:] Thesis Moritz Beckmann (<http://bib-pubdb1.desy.de/record/155874>)



Laser-Compton Polarimeters

Spin Tracking

Collision Data



Polarized Cross Section

- Theoretical polarized cross section:

$$\sigma(P_{e-}, P_{e+}) = \frac{(1-P_{e-})}{2} \frac{(1-P_{e+})}{2} \cdot \sigma_{LL} + \frac{(1+P_{e-})}{2} \frac{(1+P_{e+})}{2} \cdot \sigma_{RR} \\ + \frac{(1-P_{e-})}{2} \frac{(1+P_{e+})}{2} \cdot \sigma_{LR} + \frac{(1+P_{e-})}{2} \frac{(1-P_{e+})}{2} \cdot \sigma_{RL}$$

- Measured polarized cross section:

$$\sigma(P_{e-}, P_{e+}) = \frac{N}{\varepsilon \cdot \mathcal{L}} = \frac{D - \langle B \rangle}{\varepsilon \cdot \mathcal{L}};$$

Statistic quantity: selected data D , number of events N

Systematic quantity: background B , selection efficiency ε ,
integrated luminosity $\mathcal{L}$

- Cross section of the 4 polarization configurations

$$\sigma_{--} := \sigma(-|P_{e-}|, -|P_{e+}|)$$

$$\sigma_{++} := \sigma(+|P_{e-}|, +|P_{e+}|)$$


$$\sigma_{-+} := \sigma(-|P_{e-}|, +|P_{e+}|)$$

$$\sigma_{+-} := \sigma(+|P_{e-}|, -|P_{e+}|)$$




Previous Single $W^\pm$, Z , γ Study: Leading Diagrams


Single W^+






Single W^-



Single Z



Single γ



Consider Correlated Uncertainty

Implementing correlated uncertainty:

$$\chi^2 = \sum_{\text{process}} \sum_{i \in \pm\pm} \frac{(\sigma_i^{\text{data}} - \sigma_i^{\text{theory}})^2}{\Delta\sigma_i^2} \longrightarrow \sum_{\text{process}} (\vec{\sigma}_{\text{data}} - \vec{\sigma}_{\text{theory}})^T \Xi^{-1} (\vec{\sigma}_{\text{data}} - \vec{\sigma}_{\text{theory}})$$

$$\vec{\sigma} := (\sigma_{-+} \quad \sigma_{+-} \quad \sigma_{--} \quad \sigma_{++})^T$$

$$\Xi := \Xi_N + \Xi_B + \Xi_\varepsilon + \Xi_{\mathcal{L}}; \quad \text{e.g. } (\Xi_\varepsilon)_{ij} = \text{corr}(\vec{\sigma}_i^\varepsilon, \vec{\sigma}_j^\varepsilon) \frac{\partial \vec{\sigma}_i}{\partial \varepsilon_i} \frac{\partial \vec{\sigma}_j}{\partial \varepsilon_j} \Delta \varepsilon_i \Delta \varepsilon_j$$

Occurrence of correlated uncertainties:

- ▶ Fast switch between $\sigma_{\pm\pm}$
- ▶ Faster than change in e.g. $\delta\mathcal{L}$
- $\Delta\sigma_{\pm\pm}(\Delta\mathcal{L})$ becomes correlated
- ⇒ $\text{corr}(\vec{\sigma}_i^{\mathcal{L}}, \vec{\sigma}_j^{\mathcal{L}}) \neq 0 \quad \forall i \neq j$

Consider disadvantageous situation:

- ▶ $\varepsilon = 0.6$
- ▶ $\Delta\varepsilon/\varepsilon = 0.01$
- ▶ $\Delta\mathcal{L}/\mathcal{L} = 0.001$
- Studying the impact of correlations

Outlook

▶ Open issues

- ▶ Implementing fiducial cuts for all processes → correct description of all systematics
- ▶ Including a complete background analyses

▶ Further Improvement

- ▶ Consider also differential cross sections
- ▶ Study the possibility to use fiducial and differential cross sections simultaneously

