

A data science platform to enable time-domain astronomy

MICHAEL W. COUGHLIN,¹ JOSHUA S. BLOOM,^{2,3} GUY NIR,^{2,3} SARAH ANTIER,⁴ THEOPHILE JEGOU DU LAZ,⁵
STÉFAN VAN DER WALT,⁶ ARIEN CRELLIN-QUICK,⁷ THOMAS CULINO,⁸ DMITRY A. DUEV,⁷ DANIEL A. GOLDSTEIN,⁷
BRIAN F. HEALY,¹ VIRAJ KARAMBELKAR,⁵ JADA LILLEBOE,¹ KYUNG MIN SHIN,⁹ LEO P. SINGER,¹⁰ TOMÁS AHUMADA,⁵
SHREYA ANAND,⁵ ERIC C. BELL,¹¹ RICHARD DEKANY,¹² MATTHEW J. GRAHAM,⁵ MANSI M. KASLIWAL,⁵
IVONA KOSTADINOVA,⁵ R. WEIZMANN KIENDREBEBO,^{1,4,13} SHRINIVAS R. KULKARNI,¹⁴ SYDNEY JENKINS,¹⁵
NATALIE LEBARON,² JAMES D. NEILL,⁵ B. PARAZIN,^{1,16} JULIEN PELOTON,¹⁷ REED RIDDLE,¹² BEN RUSHOLME,¹⁸
JAKOB VAN SANTEN,¹⁹ JESPER SOLLERMAN,²⁰ ROBERT STEIN,⁵ D. TURPIN,²¹ AVERY WOLD,¹⁸ CARLA AMAT,⁸
ADRIEN BONNEFON,⁸ ADRIEN BONNEFOY,⁸ MANON FLAMENT,⁸ FRANK KERKOW,¹ SULEKHA KISHORE,⁵ SHLOKE JANI,¹
STEPHEN K. MAHANTY,¹ CÉLINE LIU,⁸ LAURA LLINARES,⁸ JOLYANE MAKARISON,⁸ ALIX OLLIÉRIC,⁸ INÈS PEREZ,⁸
LYDIE PONT,⁸ AND VYOM SHARMA¹

¹*School of Physics and Astronomy, University of Minnesota, Minneapolis, Minnesota 55455, USA*

²*Department of Astronomy, University of California, Berkeley, CA 94720, USA*

³*Lawrence Berkeley National Laboratory, 1 Cyclotron Road, MS 50B-4206, Berkeley, CA 94720, USA*

⁴*Artemis, Observatoire de la Côte d'Azur, Université Côte d'Azur, Boulevard de l'Observatoire, 06304 Nice, France*

⁵*Division of Physics, Mathematics, and Astronomy, California Institute of Technology, Pasadena, CA 91125, USA*

⁶*Berkeley Institute for Data Science, University of California Berkeley, Berkeley, CA 94720, USA*

⁷*Weights and Biases, Inc., 1479 Folsom Street, San Francisco, CA 90063, USA*

⁸*ESILV - École Supérieure d'Ingénieurs Léonard de Vinci, Paris, France*

⁹*EnergyHub, Inc., 41 Flatbush Ave, Suite 400A, Brooklyn, NY 11217, USA*

¹⁰*Astroparticle Physics Laboratory, NASA Goddard Space Flight Center, Code 661, Greenbelt, MD 20771, USA*

¹¹*DIRAC Institute, Department of Astronomy, University of Washington, 3910 15th Avenue NE, Seattle, WA 98195, USA*

¹²*Caltech Optical Observatories, California Institute of Technology, Pasadena, CA 91125, USA*

¹³*Laboratoire de Physique et de Chimie de l'Environnement, Université Joseph KI-ZERBO, Ouagadougou, Burkina Faso*

¹⁴*Owens Valley Radio Observatory 249-17, California Institute of Technology, Pasadena, CA 91125, USA*

¹⁵*Department of Physics, Massachusetts Institute of Technology, 77 Massachusetts Ave., Cambridge, MA 02139, USA*

¹⁶*Northeastern University, Boston, MA 02115, USA*

¹⁷*IJCLab, Univ Paris-Saclay, CNRS/IN2P3, Orsay, France*

¹⁸*IPAC, California Institute of Technology, 1200 E. California Blvd, Pasadena, CA 91125, USA*

¹⁹*Deutsches Elektronen-Synchrotron DESY, Platanenallee 6, 15738 Zeuthen, Germany*

²⁰*The Oskar Klein Centre, Department of Astronomy, Stockholm University, AlbaNova, SE-10691, Stockholm, Sweden*

²¹*Université Paris-Saclay, Université Paris Cité, CEA, CNRS, AIM, 91191, Gif-sur-Yvette, France*

ABSTRACT

SkyPortal is an open-source platform designed to efficiently discover interesting transients, manage follow-up, perform characterization, and visualize the results, all in one application. By enabling fast access to archival and catalog data, cross-matching heterogeneous data streams, and the triggering and monitoring of on-demand observations for further characterization, **SkyPortal** has been operating at scale for >2 yr for the Zwicky Transient Facility Phase II community, with hundreds of users, containing tens of millions of time-domain sources, interacting with dozens of telescopes, and enabling community reporting. While **SkyPortal** emphasizes rich user experiences (UX) across common frontend workflows, recognizing that scientific inquiry is increasingly performed programmatically, **SkyPortal** also surfaces an extensive and well-documented API system. From backend and frontend software to data science analysis tools and visualization frameworks, the **SkyPortal** design emphasizes the re-use and leveraging of best-in-class approaches, with a strong extensibility ethos. For instance, **SkyPortal** now leverages ChatGPT large-language models (LLMs) to automatically generate and surface source-level human-readable summaries. With the imminent re-start of the next-generation of gravitational wave detectors, **SkyPortal** now also includes dedicated multi-messenger features addressing the requirements of rapid multi-messenger follow-up: multi-telescope management, team/group organizing interfaces, and cross-matching of multi-messenger data streams with time-domain optical surveys, with interfaces sufficiently intuitive for the newcomers to the field. This paper focuses on the detailed im-

plementations, capabilities, and early science results that establishes **SkyPortal** as a community tool ready to take on the data science challenges and opportunities presented by this next chapter in the multi-messenger era.

1. INTRODUCTION

The proliferation of data from synoptic sky surveys affords an ever-increasing discovery potential in time-domain astrophysics, on solar system, galactic, and extragalactic scales. However, for this potential to be fully and efficiently realized, the volume, velocity, and heterogeneity of such data must be managed, curated, and coordinated. And, as often discovery requires more data for novel insights, new sky events demand an optimization of followup observations across a growing array of precious and loosely federated resources. We now recognize the need to change how astronomers analyze these data sets, with the application of data science principles to facilitate discovery and new insights.

Multi-messenger astronomy, with the integration of data sets from e.g., Advanced LIGO (Aasi et al 2015) and Advanced Virgo (Acernese et al 2015) for gravitational waves, e.g., IceCube (Aartsen et al. 2017) for neutrinos, e.g., the Zwicky Transient Facility (ZTF) (Bellm et al. 2019; Graham et al. 2019; Dekany et al. 2020; Masci et al. 2019) and the forthcoming Vera C. Rubin Observatory (Ivezić et al. 2019) for optical astronomy, and γ -ray survey instruments such as the *Neil Gehrels Swift Observatory* mission (Gehrels et al. 2004) and Fermi’s Gamma-ray Burst Monitor (Fermi-GBM) (Meegan et al. 2009), is unique and demanding for the number of integrated sources of data it requires to study targeted systems. As its quintessential example, the detection of GW170817 (Abbott et al. 2017a) and its associated electromagnetic transients AT2017gfo (Coulter et al. 2017; Smartt et al. 2017; Abbott et al. 2017b) and GRB170817A (Goldstein et al. 2017; Savchenko et al. 2017; Abbott et al. 2017c) have demonstrated the power of multi-messenger astronomy for measurements of the Hubble constant (Coughlin et al. 2020a,b; Abbott et al. 2017; Hotokezaka et al. 2019; Dietrich et al. 2020), the neutron star equation of state, and r -process nucleosynthesis (Chornock et al. 2017; Coulter et al. 2017; Cowperthwaite et al. 2017; Pian et al. 2017; Rosswog et al. 2017; Rosswog et al. 2018; Smartt et al. 2017; Watson et al. 2019; Kasliwal et al. 2019) amongst many other science cases.

Previously, the large sky area of gravitational-wave localizations made searching for (and doing science with) counterparts particularly challenging (e.g., Andreoni et al. 2019; Coughlin et al. 2019a; Goldstein et al. 2019; Gomez et al. 2019; Lundquist et al. 2019; Anand et al. 2020; Ackley et al. 2020; Andreoni et al.

2020a; Antier et al. 2020; Gompertz et al. 2020; Kasliwal et al. 2020). While localization accuracies should improve somewhat (Petrov et al. 2022) in the fourth LIGO-Virgo-KAGRA observing run (O4; Coughlin 2020), continued innovation in how searches are conducted remain paramount. To this end, we have undertaken an effort to integrate the capabilities from two “Marshals,” so named as software stacks designed to marshal candidates to follow-up telescopes, used during the third Observing run (O3): the Global Relay of Observatories Watching Transients Happen (GROWTH) **Target of Opportunity Marshal** (Coughlin et al. 2019b) and the Global Rapid Advanced Network Devoted to the Multi-messenger Addicts (GRANDMA) Interface and Communication for Addicts of the Rapid follow-up in multi-messenger Era (iCARE) platforms (Antier et al. 2019), within **SkyPortal**, the open-source Marshal currently employed in ZTF Phase II (van der Walt et al. 2019).

In this paper, we describe the components built within **SkyPortal**, focusing on their applications to multi-messenger astronomy. There are two existing extensions of **SkyPortal** heavily relying on these features: (i) **fritz**¹: the platform used by the ZTF collaboration for Phase II operations and (ii) **icare**²: the platform used by the GRANDMA collaboration. We describe our perspective on the time-domain ecosystem and how **SkyPortal** fits in it in Sec. 2. The key features and technical implementation of the platform are discussed in Sec. 3. Example results from the platform applied to ongoing γ -ray burst (GRB) searches are shown in Sec. 4. We summarize our conclusions and future outlook, including our perspectives on software development in an academic environment, in Sec. 5.

2. THE TIME-DOMAIN SOFTWARE ECOSYSTEM

We briefly review the time-domain software ecosystem here, and encourage interested readers to explore the references to understand this continually evolving ecosystem. Our vision for the role of **SkyPortal** in this ecosystem is presented by Figure 1. We suggest reading Street et al. (2018) for a related perspective based on experiences with the Target and Observation Manager (TOM) Toolkit, Schüssler et al. (2021) for **Astro-COLIBRI**, a platform which seeks to combine public data sets, and

¹ <https://github.com/fritz-marshall/fritz>

² <https://github.com/grandma-collaboration/icare>

Coulter et al. (2023) for YSE-PZ, a similar software stack to that presented here. The flowchart indicates the inter-related chains of research infrastructure, both hardware and software, within which SkyPortal functions.

The first key piece of the software ecosystem are brokers like Fink (Möller et al. 2020) or ALerCE (Förster et al. 2021), which ingest alerts from optical surveys such as ZTF (Bellm et al. 2019; Graham et al. 2019) or Rubin Observatory (Ivezić et al. 2019) and provide value-added annotations such as cross-matching with other catalogs. A purpose of a broker is to act as a layer between alert issuers and the scientific community analyzing the alert data. It exposes one or more services to help the scientists to efficiently (manually and programmatically) analyze the alert data from telescopes and surveys. Generally, brokers collect and store alert data, enrich them with information from other surveys and catalogs or user-defined added values such as machine-learning classification scores, and redistribute the most promising events for further analyses, including follow-up observations. Large-scale surveys such as ZTF and Rubin Observatory have required broker teams to design and implement new technological approaches to operate in real time on large computing infrastructures for a wide variety of science cases. Recently, Rubin Observatory announced which Community brokers will have unrestricted access to the complete alert stream for the next decade³: ALerCE (Förster et al. 2021), AMPEL (Nordin et al. 2019), ANTARES (Matheson et al. 2021), BABAMUL, Fink (Möller et al. 2020), Lasair (Smith et al. 2019), and Pitt-Google. Most of these brokers are already operating on the ZTF alert stream, which has constituted a prime opportunity to engage projects with the scientific community while preparing the ground for the upcoming Rubin Observatory alert data.

Some of these alert brokers also process alert data from other surveys and telescopes as well, including data at different wavelengths and from different messengers, and interested readers are encouraged to explore the references above for specifics. These annotations may include information from other wavelengths, spectroscopy, or historical data; they also often provide classification information, such as using machine learning classifiers that account for these annotations. All of these innovations are designed to support astronomers in purifying the alert streams to restrict the objects to those of scientific interest for particular users.

However, the role of a broker is not to ingest all the data that a user of such a broker might need for a complete analysis, as it is sometimes beyond the expertise or the roadmap of the broker team, or it would require a substantial amount of work to integrate, or simply because some data requires proprietary access. Instead, broker systems expose interoperable tools so that users can export enriched data elsewhere to continue the analysis. In practice, this is where TOMs and Marshals, for which interfaces with most brokers have been developed, come in, where the coordination of follow-up observations and further scientific analyses will take place after brokers enrich the data.

The second key piece of the software ecosystem relates to platforms whereby multi-messenger instruments (e.g., high-energy, gravitational waves, neutrinos, and transient phenomena in general) can share alerts and rapid communications; these currently include the General Coordinates Network (GCN; Singer & Racusin 2023) and the Scalable Cyberinfrastructure to support Multi-Messenger Astrophysics⁴ (SCiMMA) project. These projects serve to ingest and then re-distribute these alerts to subscribing astronomers in the community. In this sense they are similar to brokers, although in general do not seek to annotate the ingested data streams, as the brokers do; it is again TOMs and Marshals that are often ingesting these streams, although some brokers also enable alert stream cross-matching with these multi-messenger notices.

TOM systems interact with both brokers and these multi-messenger alert distribution systems. While there is inevitably some redundancy with brokers especially, the focus of TOMs is to be a centralized database whereby coordination of follow-up observations of identified candidates (such as those passing the filters run within brokers) and support of astronomer science (such as integrating classification frameworks to be used on the resulting data sets) is possible. These TOM systems involve both human and algorithmic interactions, such as for the prioritization and submission of follow-up requests for target lists.

TOMs provide an important conduit for information flow within this ecosystem. While many of these services are developed independently, they rely on well-defined interfaces such as Application Programming Interfaces (APIs) to interact. For time-domain astronomy in particular, they must also interact with flexible algorithmic frameworks which can plot and fit transients such as supernovae or tidal disruption events, as well as pe-

³ <https://www.lsst.org/scientists/alert-brokers>

⁴ <https://scimma.org/>

riodic and quasi-periodic objects such as eclipsing binaries. They also need to interact with core external services to different astronomical communities such as the Transient Name Server⁵ (TNS) or the Minor Planet Center⁶ (MPC). While it is possible to downselect the services a TOM interacts with, it is inevitable that these communities overlap, given that, for example, transient astronomers are always interested in avoiding following up asteroids like those reported to the MPC.

Underlying the software components of the time-domain ecosystem are the methods by which data are stored, normalized, and exchanged. While the international standard for formatting information about astronomical transients (VOEvents; Seaman et al. 2011) is widely used, many data types in the time-domain ecosystem (like spectra, human comments on events, classifications) exist and are disseminated without a single globally recognized standard⁷. While **SkyPortal** manages heterogeneous input by enforcing data exchange with a strict API schema, the facilitation of community interactions could be more streamlined by a renewed global effort in defining schema and formats for multi-messenger data exchange.

3. SKYPORTAL FRAMEWORK

In the following subsections, we present the key features and specific, implemented subsystems of **SkyPortal** in use to enable applications in time-domain astronomy.

3.1. Alert Brokering

Several **SkyPortal** instances rely on alert brokers to populate their databases with candidates that users can scan and save as sources (or reject) for their groups. In the case of **fritz**, it uses **Kowalski**⁸, an open-source, multi-survey data archive and alert broker (Duev et al. 2019), for performing filtering and cross-matches, including rejection of bogus objects (Duev et al. 2019); some science groups also rely on **AMPEL** (Nordin et al. 2019). In the case of **icare**, it relies on ZTF-Fink (Aivazyan et al. 2022), including its filtering capabilities targeting fast transients, to select promising candidates.

3.1.1. *Kowalski*

Kowalski comprises a non-relational (NoSQL) MongoDB⁹ database to store ZTF alerts and other catalogs, and an API layer that allows external users (such as **fritz** itself, or the users using it) to interact with it. Among other benefits, MongoDB provides fast execution times ($\sim \log(N)$) for standard operations, allows for efficient positional queries, and saves individual entries in the binary JSON format—well-matched with the **AVRO** format of ZTF alerts. A dedicated **Kafka** consumer in **Kowalski** consumes the ZTF alert stream at IPAC in real-time and ingests alerts into the database, where they are stored as “documents.” **Kowalski** provides an infrastructure relying on parallel computing to filter and enhance many alerts at once prior to ingestion. Basic filters can be specified in the configuration, on top of which user-based filters can be defined for the different instruments handled by **Kowalski**. Those can be sent to **Kowalski** using its API, allowing the development of GUIs (like the dedicated filter page on **Skyportal**) where users can define filters in a human-readable JSON format (see Sec. 3.3.1).

Users define filters in the Metaweb Query Language (MQL) syntax, so that they can be run on the alerts stored in **Kowalski** as “documents.” A filter takes the form as a MongoDB “aggregation pipeline” that is tuned to a specific scientific objective. An aggregation pipeline is a list of dictionaries, each representing a specific stage in the filtering process. A stage performs an operation on the document, such as calculating a value (e.g., the age or color of the transient) or filtering the document (e.g., only pass documents with color > 1 mag.). All documents are fed to the first stage, but only the output of a stage is fed to its subsequent stage—this ensures that only documents of interest are retained by the end allowing for efficient automated filtering of alerts.

As part of the filtering document, users can specify which alert fields can be posted to **SkyPortal** as annotations, allowing for quick analysis of source properties. For alert enhancement, **Kowalski** can be configured to cross-match alerts with other catalogs and candidates from the other instruments or run machine learning inference on them. The user-defined filters are applied after the cross-matches and machine learning scores are added, meaning that filtering can be done based on those values and not only the original alert fields. Based on the filtering results, an alert sentinel will post candidates and annotations. Once the enhanced alerts are ingested into **Kowalski**’s database, users can query them by running MongoDB Query Language (MQL)-based

⁵ <https://www.wis-tns.org/>

⁶ <https://minorplanetcenter.net/>

⁷ To be sure, standards like VOTable enable unified data storage and exchanges but are generic and flexible enough to the point that the same data may be stored in a multitude of ways, ie., without a unified standard.

⁸ <https://github.com/skyportal/Kowalski>

⁹ <https://www.mongodb.com/>




Figure 1. Flowchart for the multi-messenger, technical ecosystem envisioned in this platform.

queries using Kowalski’s API. The package `penquins`¹⁰ provides a python client to interact with the Kowalski API. Kowalski is containerized using Docker allowing for simple deployment on the cloud or on-premises.

The instance of Kowalski that serves as the backend for `fritz` is deployed on-premises at Caltech. As of March 2023, it stores ~ 38 TB of data including ~ 555 million ZTF alerts and ~ 20 other catalogs (e.g., 2MASS, Cutri et al. 2003; ALLWISE, Cutri & et al. 2012). It processes millions of requests daily, received either from `fritz` or ~ 10 individual users for whom direct access is allowed. It handles candidate filtering for ~ 80 ZTF experiments (e.g., the Bright Transient Survey; Fremling et al. 2020; Perley et al. 2020) by running filters saved on `fritz` (see Sec. 3.3.1) on all new ZTF alerts in real-time. In addition to ZTF, this instance also manages the alert stream for Palomar Gattini-IR (De et al. 2020)—an infrared time domain survey—in a similar manner and may do the same for WINTER (Lourie et al. 2020). These figures are summarized in Table 2.

3.1.2. AMPEL

In addition to Kowalski, some science working groups in ZTF use AMPEL (Nordin et al. 2019) to process the alert stream and display the results on `fritz`.

¹⁰ <https://github.com/dmitryduev/penquins>

Table 1. Kowalski

Data Stored	~ 38 TB
ZTF Alerts	$\sim 5.55 \times 10^8$
Other Catalogs	~ 20

Key numbers for the Fritz instance of Kowalski instance.

Table 2. fritz

Photometry	~ 400 million
Candidates	~ 7.3 million
Sources	$\sim 420,000$
Spectra	$\sim 11,000$
Groups	~ 500
Users	~ 320
Tokens	~ 160
Filters	~ 80
Telescopes	~ 70
Instruments	~ 85
Comments	$\sim 170,000$
Annotations	~ 3.2 million
Thumbnails	~ 12.2 million
GCN events	$\sim 3,100$

Key numbers for the Fritz instance of SkyPortal

AMPEL divides its processing into four tiers. Each tier is handled by a set of *units* (pluggable, configurable modules) that each perform a specific task. At Tier 0 (*ingest*), alert packets are filtered, and selected alerts are decomposed into constituent data points (e.g., indi-

vidual photometric points) and stored. At Tier 1 (*combine*), data points are combined into *states* (e.g., light curves). At Tier 2 (*augment*), data points and states are enhanced with auxiliary or derived information, e.g., catalog matches for photometric points or model fits for light curves. At Tier 3 (*react*), documents are aggregated by *stock* (transient object being tracked) and can be reported to an external service, e.g., to request follow-up for the N most interesting objects, or simply provide a target list for a traditional scanning workflow. Users can customize each of these tiers to create a *channel*, a real-time analysis plan specific to their intended science program. This could consist of e.g., a custom alert filter, datapoint association scheme, set of light curve analyses, and reporting scheme. Tiers 0–2 are driven by the alert stream, while Tier 3 is run at fixed intervals.

AMPEL integrates with SkyPortal via SkyPortalPublisher, a Tier-3 unit distributed as part of the Ampel-ZTF package¹¹. Each stock that SkyPortalPublisher processes is saved as a candidate for a set of filters. It assumes a one-to-one mapping between AMPEL channels and (dummy) filters stored on fritz by default, but a custom set of filters may be configured instead. Additionally, a stock is saved as a source in a set of target groups if so configured. Light curve analysis results from Tier 2 are serialized to JSON and posted as comments on the source. This behavior predates the analysis platform described in Sec. 3.5.3, and we expect to migrate the analysis reporting of AMPEL to this service in the near future. If photometry and image cutouts were loaded as part of the Tier 3 process, these are posted as well. This makes it possible to use AMPEL with a standalone SkyPortal instance, but this is disabled in the ZTF instance, as competing backends tend to confuse users and lead to unnecessarily high database loads. Finally, SkyPortalPublisher keeps a record of its communication with SkyPortal in the journal associated with each stock, and only attempts to post if it was updated since the last successful attempt.

Some science programs require two-way communication, e.g., the ZTF Nuclear Transients group uses classifications that human astronomers post to Fritz in their AMPEL-based scanning workflow. AMPEL enables this via e.g., FritzReport, a Tier-3 complement stage that injects a source record from SkyPortal into stock records before they are provided to downstream units.

3.1.3. Fink

The GRANDMA collaboration uses the Fink broker (Möller et al. 2020) to select promising alerts from the

public ZTF alert data stream and display the results on icare.

The current Fink platform works in four steps. First, alerts from multiple streams are continuously ingested and stored on disk. Second, alerts satisfying the quality cuts defined by the broker team are processed by a set of science modules. These science modules—currently a dozen, spanning solar system objects to galactic and extragalactic science—are independent processing units developed by the community of users, and deployed in the Fink platform. They can work on a single input alert stream, or combine several streams together. These science modules enrich the initial alert packets using several techniques such as cross-match with external catalogs of astronomical objects, or classification using machine or deep learning based algorithms. All added-values are made public. Third, enriched alert packets are filtered based on their content, and the most promising events are redistributed to the scientific community in real-time. The filtering is again community-driven, and users design and deploy filters to receive tailored information in real-time. Finally, all enriched alert packets are stored in a database for permanent access and for further analyses. Fink exposes a number of services to the users to design modules, filters, and access the data¹².

Fink integrates with icare with the SkyPortal Fink Client¹³. Alerts are first polled using the Fink Livestream service, and then pushed to icare using core functionalities of SkyPortal. The SkyPortal Fink Client runs as an optional microservice inside icare which simplifies the deployment and the maintenance for users. We expect to migrate this optional microservice to the main SkyPortal codebase in the near future so that it can benefit the SkyPortal community at large.

In the context of GRANDMA, three specific Fink filters targeting alerts associated with fast transients have been deployed (Aivazyan et al. 2022). One of the filters is based on the output score of a dedicated science module implementing a fast transient classification algorithm, and all filters were used in two subsequent follow-up campaigns of optical transients to search for orphan kilonova (Biswas et al. 2022). Selected alerts are automatically published into icare, where continuous human scanning takes place (see below for scanning capabilities within the platform). Astronomers would then decide to trigger further observations based on the received alerts content, but also using external infor-

¹² <https://fink-broker.readthedocs.io>

¹³ <https://skyportal-fink-client.readthedocs.io>

¹¹ <https://github.com/AmpelAstro/Ampel-ZTF>

mation collected by the GRANDMA collaboration and ingested into **icare** directly by other means.

3.2. Associated software packages

By design, **SkyPortal** is open source, and through its development, changes have been contributed to open-source, upstream packages such as **sncosmo** (Barbary et al. 2016); while it would be out-of-scope to describe all of the packages on which **SkyPortal** relies, we briefly describe two such packages, **Baselayer** and **HEALPix-Alchemy** (Singer et al. 2022a), for which development is particularly coordinated.

3.2.1. Baselayer

The open-source package **baselayer**¹⁴ provides the backbone of a generic science-application web framework on top of which **SkyPortal** is built. Originally built for the open-source time-domain machine learning application **cesium** (Naul et al. 2016), **baselayer** implements, e.g., web socket communication between the backend and frontend, authentication, access control, microservices, configuration, process management, cron jobs, migrations, and external logging. As far as possible, it combines standard solutions, such as **Tornado**, **Nginx**, **supervisor**, and **Python Social Auth**, instead of implementing them from scratch. By delegating web infrastructure to **baselayer**, concerns are better separated and the **SkyPortal** team can focus on domain-specific concerns. That said, the **SkyPortal** team also contributes platform improvements upstream as required, exposing these to a wider audience.

At the core of **baselayer**, we find **sqlalchemy**¹⁵, an Object Relational Mapper (ORM) written in Python that allows easy interaction with a relational database, here being **PostgreSQL**¹⁶ (Stonebraker & Rowe 1986). Several base models—which are the abstractions of tables in the database—are defined to introduce the concept of users, permissions, roles, API tokens, and groups. An add-on of **Python Social Auth** provides the necessary models for user authentication using many **openid** authentication services. In both **baselayer** and **SkyPortal**, authentication through Google services is the method of choice. **sqlalchemy** also allows handling multiple parallel and separate connections to the database named sessions. This is an important requirement for any API-based application, where multiple users need to read/write/modify/delete from the database simultaneously. Wherever interact-

ing with the database is necessary, we open a session, add/modify/delete from that session, and then commit the changes. Changes are made to the database only once the commit method is called, and **PostgreSQL** is capable of resolving conflicts between multiple commit sessions if necessary.

For the users to interact with the API-based application that is **baselayer**, we define API Handlers, which are simply python classes with the standard GET, POST, DELETE, PUT, and PATCH method an API is expected to have. Then, **Tornado** maps each handler to the associated API endpoint. It is capable of calling the right API method of the handler and passing in-path parameters for each API call. In **SkyPortal**, everytime a new feature is needed, database models and handlers to interact with them can be added to the application following the same process. When it comes to permissions, **baselayer** provides python decorators that can be specified above each API method to specify what permissions or roles a user needs to use it. Similarly, database-level access restrictions can be defined in every **sqlalchemy** model, to ensure that users only have access to the data points that have been shared with them or with the groups they belong to.

Using a microservice architecture managed with **supervisord**, we can run multiple instances of the application in parallel to ensure availability and reduce downtime. That way, the app can easily scale horizontally based on the number of users or when new features are added. Moreover, we can add microservices to run background operations continuously. In **baselayer**, this is used to run the application of course, but also the database migration manager, the webpack builder, web-socket server, cron jobs, external logging, and **nginx**. In **SkyPortal**, this has been proven to be extremely useful when adding computationally expensive or long-running features such as the ingestion of GCN events with low latency, processing of observation plans, sending notifications and reminders, and programming recurrent API calls. These services will be discussed in further detail later in this paper.

3.2.2. HEALPix-Alchemy

To ensure calculations are sufficiently computationally expedient in **SkyPortal**, we represent the complex geometry of regions of interest (such as multi-messenger skymaps) and the instruments’ fields of view using the Hierarchical Equal-Area isoLatitude Pixelization (HEALPix; Górski et al. 2005) framework; to this end, we have developed a **PostgreSQL** extension enabling **HEALPix**-based cross-matches to make rapid processing on these large alert databases possible (Singer

¹⁴ <https://github.com/cesium-ml/baselayer>

¹⁵ <https://www.sqlalchemy.org/>

¹⁶ <https://www.postgresql.org/>




Figure 2. An example of the multi-resolution HEALPix sampling scheme for tiling localizations. The left panel shows an example heat map image representing the localization probabilities; darker, deeper colors represent higher probability density. The middle panel shows the boundaries of the multi-resolution HEALPix tiles on which the sky map was sampled. The right panel shows potential telescope field of views covering that skymap.

et al. 2022a), named **Healpix-Alchemy**. We briefly describe the innovation and its use within **SkyPortal** here, and encourage readers of this paper to see [Singer et al. 2022a](#) for further details.

In version 14, PostgreSQL introduced a new *multi-range* type, consisting of an array of ranges, with a fast aggregation function, which takes ranges as its input and returns their union as a multirange; when combined with the multi-order-coverage (MOC) representation of sky maps ([Fernique et al. 2014](#)), this tandem yields highly efficient database-side processing of skymap overlaps.

Most multi-messenger events do not provide us with a precise localization to observe, but instead a map of probability density (see e.g., Fig. 2) using MOC to divide the sky into tiles of diverse resolutions. Each tile has an associated probability density that the event occurred in it. MOC uses the HEALPix tessellation algorithm to divide the spherical observable sky into 12 diamond shapes of equal area. Each of them can be recursively divided into 4 to obtain the level of resolution needed to represent the variation of probability from one point of the sky to another; recursively dividing these tiles into 4 sub-diamonds increases the order and therefore the resolution.

At order 0, tiles have indexes from 1 to 12, and at order 1, from 1 to 64. For instance, tile 1 at order 0 is now made of tiles 1 to 4 at order 1, and tiles 1 to 16 at order 2, and so on recursively until the highest order is order 29, where a tile side size is only 0.38 milli-arcseconds; this minimum resolution is set by requiring that the corresponding pixel index can be stored as a 64 bit signed integer without overflow. Thanks to the recursive indexing schemes of the HEALPix algorithm, when saving MOC maps in the database, we can represent each tile as the range of tiles that it is composed

of at order 29. This is convenient as it allows us to represent tiles as a probability density associated with a range set. To do so, **Healpix-Alchemy** combines the power of Healpix and SQLAlchemy, a python package used to communicate with PostgreSQL databases using python. **Healpix-Alchemy** uses the range sets feature of PostgreSQL databases to represent tiles and single points with 64 bits integers and provides the tools necessary to cross-match tiles and points. For software stacks that rely on relational databases, this range sets representation of HEALPix tiles is the best (and only viable) implementation to perform rapid spatial queries.

As MOC has become the standard representation for skymaps in multi-messenger astronomy ([Fernique et al. 2022](#)), **Healpix-Alchemy** enables efficient queries of instrument footprints for rapid cross-matches with historical γ -ray burst, neutrino, and gravitational-wave skymaps. Similarly, based on the coordinates of any object, observation, or galaxy, **SkyPortal** calculates and stores its associated HEALPix index at order 29 (which is the highest order, as stated above). This means that the spatial cross-match between sources, galaxies, and multi-messenger events is performed simply by looping over the localization tiles of an event localization to perform trivial intersection operations. Furthermore, thanks to the range set representation of PostgreSQL, performing the intersection and union of the HEALPix tiles representing regions of space is equivalent to a simple merging of sorted lists of integers ([Singer et al. 2022b](#)). These intersection operations indicate if a given HEALPix index (a point) is contained in any of the range sets of the indexes corresponding to HEALPix tiles (a spatial region).

Using the same mechanism as the sky maps, **SkyPortal** also represents instrument fields using MOC

representations of their footprint on the sky. The same basic union operations can be performed to determine which portions of a sky map (or in principle, objects and galaxies) an instrument is able to observe. Because the HEALPix algorithm has limits in resolution, the usage of MOC to define circles, polygons, and other objects with a basic geometry is in some sense an approximation (Fernique et al. 2015), nevertheless, the MOC standard is an efficient way of representing instrument fields in a compact and generic manner.

3.3. Point Source Features

While the line between features designed to interact with individual point sources and those designed to describe and interact with larger areas of the sky is blurry, we still find it useful as a broad diagnostic for understanding subsets of the features. Here, we describe the workflow for studying individual sources, from filtering to photometry to follow-up.

3.3.1. Filters and Scanning

With a full night of observing, ZTF sends $\sim 600,000$ – $1,200,000$ alerts per night, with over 2,000,000 alerts sometimes possible (Patterson et al. 2018); for comparison, Rubin Observatory expects to send $\sim 10,000,000$ alerts per night. Given that the overwhelming majority of these alerts are not of interest to the average user, a combination of automated filtering and human scanning is used to reduce the alert list to a short list of sources deemed worthy of further attention.

Within **SkyPortal**, every science objective has a dedicated “group” of users, and one associated filter per group. These filters are defined within the brokers described in Section 3.1. For **Fritz** in particular, an “upstream” aggregation pipeline that combines all photometric history, cross-match data, and ML scores for a ZTF alert available in **Kowalski** into a single document is run and then passed to the user-defined filter. Filters saved on **Fritz** are version controlled and can be viewed/updated on a dedicated tab.

As brokers are filtering the alert stream automatically in real-time, sources producing alerts that pass a given filter are known as *candidates*. **SkyPortal** can be configured to immediately save all candidates that pass the filter to a group (a collection of sources), but in most cases, users will prefer to manually vet the stream to separate sources of genuine interest from false positives in a process referred to as candidate scanning. All candidates passing a filter during a chosen time period (e.g., the past 24 hours or the past 3 nights) can be displayed rapidly on the Candidates page. This page displays image cutouts for each candidate location from ZTF and

other surveys, along with light curves and some additional information (coordinates, TNS cross-matches, etc.) and links to other resources. The user can peruse this list of candidates and save only those of interest based on this additional information. Candidates that are not saved will reappear if the source continues to produce alerts that pass the filter in the future, but the user can also choose to hide any sources that are clearly false positives from their future scanning efforts.

3.3.2. Photometry, Spectroscopy, and Photometric Series

In addition to ingestion of photometry from alert streams provided by brokers, **SkyPortal** benefits from both public photometry services from Pan-STARRS Data Release II (Chambers et al. 2016; Flewelling 2018) and forced photometry services of both ZTF (Masci et al. 2019) and ATLAS (Tonry et al. 2018; Smith et al. 2020). These are available for querying through their API services. The visualization interface for photometry has been described previously (van der Walt et al. 2019), but briefly, it is a **Bokeh** (Bokeh Development Team 2018) implementation that allows one to view either magnitude or flux as a function of time, with tooltips providing basic information about the individual photometry points. There is also a panel that allows the user to specify a potential period to phase-fold the photometry, in case of periodic sources.

Statistics on each source are collected and updated upon the insertion of new data points. This includes, e.g., the brightest magnitude, the time when the source was last detected, and so on. These statistics are updated on insertion to avoid the costly re-calculation over hundreds of data points per source (in **fritz**, there is currently an order of 4×10^8 individual photometry points across all sources). Such statistics are used to quickly filter sources based on their light curves, without needing to calculate each statistic for each source in each query.

Another way to store large photometric datasets has recently been added to **SkyPortal**: the photometric series. This data product will be used by surveys with very high cadences and continuous coverage of the same field, e.g., the Transiting Exoplanet Survey Satellite (TESS; Ricker et al. 2014) takes images at a maximum cadence of 20 s over 27-day series. In this case, saving each of the $\sim 10^5$ data points as individual rows in the database becomes unmanageable, both in terms of storage and in terms of communicating the data in and out of **SkyPortal**. Instead, we store the underlying data as HDF5 files and keep a queryable record in the main database of the file (along with some statistics).

Spectra are uploaded either manually or via API. The spectra are associated with each source but the platform also enables the users to provide comments, allowing users to discuss either the source or the individual spectra. There are also standard line lists available to perform line identification, enabling classification.

3.3.3. Finding Charts and Starlists

To aid the rapid followup of sources of interest, **SkyPortal** enables photometric and spectroscopic finding charts to be generated on the fly. In interactive mode, a user selects a catalog image from DESI DR8, ZRF Reference Images, DSS2, or PS1, image size, and number of spectroscopic offset stars. Using a flux-weighted median position from all photometric detections, up to 4 nearby isolated stars from Gaia DR3 are selected as spectroscopic offset stars. The offsets are calculated using the parallax and proper motion of the stars from Gaia DR3 assuming the current datetime as the observing epoch. These offset stars can be copied from the frontend in different starlist formats. The finding charts can be generated programmatically and from the frontend (single click) with default parameters. A downloadable PDF is assembled and cached to facilitate fast observing run organization.

3.3.4. Periodograms

For variable stars, **SkyPortal** enables an interactive periodogram analysis. An adapted javascript version of the Generalized Lomb-Scargle implementation (Zechmeister & Kürster 2009) allows for client-side computation of the periodogram. A user can change photometry filters and interactively select trial periods as well as visualize the folded light curve on the selection period and period aliases.

3.3.5. Source Classifications

SkyPortal offers a classification system that lets users tag sources with relevant labels. The namespace for classifications is set by taxonomies, which are collections of labels connected with each other using nested JSON format. **SkyPortal** sets a default Sitewide Taxonomy for use in all groups on the application based on the `tdtax`¹⁷ repository. Users can also post custom taxonomies (that adhere to a strict taxonomy schema) to specific groups, limiting their classifications’ visibility to members of those groups. Each classification has an associated probability that quantifies confidence in the label.

¹⁷ <https://github.com/profjsb/timedomain-taxonomy>

Figure 3. JSON-based follow-up interface.

Based on the system built within the ZTF Variable star Marshal (van Roestel et al. 2021; Coughlin et al. 2021), **SkyPortal** allows users to post classifications from a drop-down menu one by one or use a slider interface that facilitates faster labeling. The slider interface initially shows the top-level classifications of the selected taxonomy. Each classification is accompanied by a slider to adjust its probability. If the slider of a classification is moved to a non-zero probability, the child classifications of the parent will be shown along with additional sliders. This interface allows multiple classifications to be posted at once.

SkyPortal also features a classification voting system that facilitates collaborative labeling of sources in a prompt but informative way. Users can express their confidence in each existing classification visible to them by casting a thumbs “up” or “down” vote. When a user adds or deletes a source’s classification or casts a vote, **SkyPortal** marks the source as “Labeled.” The user can later choose to view only unlabelled sources in a group to allow quick resumption of the labeling process.

3.3.6. Follow-up

From within **SkyPortal**, API-based triggered is available for the telescope of the Las Cumbres Observatory network (Street et al. 2018), the Katzman Automatic Imaging Telescope (KAIT; Li et al. 2003), the Liverpool Telescope (LT; Steele et al. 2004), Swift (Gehrels et al. 2004), the SED Machine (SEDM; Blagorodnova et al. 2018; Rigault, M. et al. 2019) on the Palomar 60 inch (P60) telescope, and the wide-field infrared transient explorer (WINTER; Lourie et al. 2020). Adding a new telescope follow-up capability is straightforward. Figure 3 shows an example drop-down menu customized for SEDM.

Groups that scan for candidates within **SkyPortal** often use the same platform to trigger photometric and spectroscopic follow-up in the same portal. Priorities, time-windows, and observational set-ups can be selected and edited. Once the data has been obtained, some systems such as the robotic SED Machine (Blagorodnova et al. 2018), automatically reduce (Rigault, M. et al. 2019) and upload the spectra for visualization. In the case of **fritz**, if a source spectrum is automatically matched to a thermonuclear spectrum (SNIa; Fremling et al. 2021), those spectra and classifications are also directly uploaded to the TNS. For other sources, human interaction allows for the classification (or rescheduling) of other targets, as well as the inclusion of detailed comments and discussions to share results and collaborate on particular objects.

3.4. *Non-point Source and Multi-messenger Features*

While many of the features described above have applicability to sources of all types, including infrastructure for follow-up, some of the features have been developed focusing on interactions with larger areas of the sky, as appropriate for many multi-messenger science cases. Here, we describe those features, focusing on their applicability for supporting multi-messenger source analysis and follow-up.

3.4.1. *GCN Events*

Much of the existing infrastructure for communicating multi-messenger observations originated from the GRB detection community in the 1990s (Barthelmy et al. 1995), with the decades-old “Gamma-Ray Coordinates Network” (GCN) continuing to play a central role in modern time-domain astronomy. This system includes the machine-readable “GCN Notices,” which uses three legacy communication formats (text, binary, and VO-Events; Allan et al. 2017), each with its own communication protocols. Recently, there have been concerted efforts to reimagine this system as a modern “General Coordinates Network,” transitioning to a unified communication protocol using open-source Apache Kafka, with the ultimate aim of relaying all data via the industry-standard JSON format¹⁸.

SkyPortal is fully integrated with this new GCN Kafka format and can ingest notices shared via this protocol. Which of the available streams should be ingested is specified in the configuration of the application. These GCN notices typically contain either full MOC sky maps (Fernique et al. 2022), coordinates in right ascension and declination along with an associated error radius, or the

vertices of a region shaped like a polygon. In all cases, a new entry is added to the database containing the localization itself (transformed to a MOC for efficient and standardized queries) and other available event properties such as localization area, median distance, or astrophysical probability. These events then can be subsequently queried, cross-matched to sources or galaxies, and used to coordinate subsequent follow-up.

SkyPortal supports the analysis of these events by allowing for different queries within the localization map: telescope observation footprints, galaxies, and transient sources. The analysis page of each event can display the error regions in a spherical projection, and can additionally display the results of the queries (see an example in Fig. 4). Moreover, the sources returned in the query will appear listed in the *Sources* table of the event page, enabling further visual inspection. The live interaction that occurs in the *Sources* menu has shown to be essential to enable candidate vetting and follow-up prioritization. For example, by clicking the arrow next to the name of the source or candidate, **SkyPortal** displays the available photometry, as well as cutouts of the coordinates of the source. Once a candidate association has been confirmed or ruled out, its status can be updated and comments can be left for future reference or internal communication amongst collaborators. Finally, **SkyPortal** can use this information to generate automated GCN circulars which summarize observations performed by telescopes that overlap the event, the associated sources detected by those observations, and the estimated event localization probability covered by those observations.

3.4.2. *Observation: Planning and Execution*

A central component of multi-messenger astronomy is the efficient coordination of follow-up for a given event, especially for gravitational-wave and GRB triggers which are initially poorly localized. Astronomers may have access to both wide field-of-view instruments and narrow field-of-view instruments of different depth and wavelength coverage. Developing strategies for optimal follow-up with a particular telescope has been an area of active research in recent years (e.g., Coughlin et al. 2018, 2019c; Almualla et al. 2020).

SkyPortal has extensive functionality to automatically perform these optimizations in a user-friendly GUI. Upon ingestion of localizations, **SkyPortal** can generate optimized observing schedules using the open-source “Gravitational-wave Electromagnetic Optimization” (**gwemopt**) software package (Coughlin et al. 2018, 2019c). **gwemopt** can generate custom plans for individual telescopes, or broader network plans which co-

¹⁸ <https://gcn.nasa.gov/>




Figure 4. GCN Page - Analysis Section: here, users can visualize the localizations associated with an event, and query the sources, galaxies, instrument tiles (for a given allocation on an instrument), and observations contained in the different localizations, while restraining their searches based on several parameters: cumulative probability, number of detections, distance in Mpc, and first and last detection dates. Other features accessible in this section allow to query catalogs of candidates from different alert brokers, run simulations with *simsurvey*, and generate text-based summaries similar to GCN circulars with added version control. It is also possible to submit the executed observations to *treasuremap.space* (Wyatt et al. 2020). Side panels can be opened that contain the properties of the event and localizations, lightcurves, GCN notices and circulars, as well as a comment section for users to communicate their results.

ordinate multiple telescopes simultaneously. It can either generate an agnostic sky-tiling schedule, or use internal catalogs to generate a galaxy-targeting schedule while accounting for user-tunable factors such as air-mass, start and end time, or available filters.

Plans are typically generated by default at the time of event ingestion, with the option for further plan generation via a configurable web form. Each of these plans can be visualized on the event page, overlaid with the initial localization. Observation plans can be triggered automatically, but can also be triggered manually from the GCN Event page.

To assess the efficacy of the generated plans, we use the open-source simulator software *simsurvey*¹⁹ (Feindt et al. 2019) (and are working with the author of *skysurvey* to integrate it²⁰). In particular, we use *simsurvey* to simulate transients of various types (kilonovae, GRB afterglows, supernovae, etc.) to estimate the probability of detecting one of these transient types

within the skymap, given the proposed observation plan. For kilonovae, the optical/NIR counterparts to binary neutron star mergers generated from the radioactive decay or *r*-process elements (Metzger 2017), we use a POSSIS-based (Bulla 2019) grid of kilonova models spanning the plausible parameter space for kilonovae from binary neutron star and neutron star–black hole mergers (Dietrich et al. 2020; Bulla 2023). For GRB afterglows, we use *afterglowpy* (Ryan et al. 2020), an open-source computational tool modeling forward shock synchrotron emission from relativistic blast waves as a function of jet structure and viewing angle. This analysis accounts for properties of the skymaps (i.e., probability in right ascension and declination, distance in the case of gravitational-wave skymaps), as well as properties of the observations (i.e., right ascension and declination for each field, observation time, limiting magnitude, filters, etc.).

To send back data from the observations based on these plans, telescope teams can use the API of *SkyPortal*, or add them directly on the Observation Page. Observation plans will automatically be cross-matched with the newly added observations, so they

¹⁹ <https://github.com/ZwickyTransientFacility/simsurvey>

²⁰ <https://github.com/MickaelRigault/skysurvey>

Figure 5. GCN Page - Observation planning: here, users select an allocation, the fields of the instrument of the allocation that overlap with a localization, as well as pick the parameters to use from the MMA API class of the instrument. Multiple observation plans can be created simultaneously and combined if necessary. Moreover, buttons allow users to download observability and airmass charts, as well as recompute airmass in real time to show which tiles of the skymap are observable. It is also possible to submit the proposed observations to `treasuremap.space` (Wyatt et al. 2020). Once created, all observation plans will be listed by instrument, where they can be updated, sent, or deleted to/from an instrument queue.

can appear on the list of observation plans for the event. If all observations scheduled in a plan are finished, the observations will be labeled as completed. Due to the elusive (red and fast-fading) nature of gravitational wave and GRB counterparts, several consecutive follow-up campaigns could result in a limited number of counterpart detections. Thus, one of the main science cases in multi-messenger astronomy is using upper limits to constrain transient properties (Coughlin et al. 2019d, 2020c). To quantify our sensitivity to electromagnetic counterparts from our past observations, we again use `simsurvey`. We inject light curves consistent with the distance and location information contained in the skymaps and calculate the detection efficiency (i.e., the ratio between the number of detected transients and the number of injected transients) based on the field-by-field limiting magnitudes of our uploaded observations. We can then report these detection efficiencies, along with the median depth of our observations promptly via GCN.

3.4.3. Galaxy Catalogs

Due to the relatively local nature of multi-messenger astronomy, both follow-up focusing on galaxy cata-

logs (Arcavi et al. 2017; Valenti et al. 2017) and comparison of transient locations to catalogs is important. Within the database, galaxies can have several attributes: name, alternative name, catalog name, RA, Declination, redshift (z), and distance in Mpc (if known), as well as other properties and their associated margin of error if provided. Concerning the usage of catalogs, in `fritz`, we use the Census of the Local Universe (CLU) (Cook et al. 2017) catalog, which is complete to 85% in star formation and 70% in stellar mass at 200 Mpc; this catalog currently remains proprietary. In `icare`, GLADE+ (Dalya et al. 2021), an open-source catalog containing more than 22 million galaxies, complete up to 44 Mpc and nearly 90% complete at even 500 Mpc, is used. The latter is a combination of six separate astronomical catalogs: GWGC, 2MPZ, 2MASS XSC, HyperLEDA, and WISEXSCOSPZ. While we focus on these two catalogs, the API interface makes ingestion of other galaxy catalogs (and therefore cross-matching) straightforward, with a minimal requirement of right ascension, declination, and galaxy name. As one can imagine, the large size of these catalogs drives the need to perform efficient cross-matches between objects, multi-messenger event localizations, and these galax-

ies; our innovations with **Healpix-Alchemy** has helped, however, these are challenges that we are still working on to date, with performance improvements in the roadmap for O4. However, initial versions suitable for production performance are already implemented and functional.

3.5. Interpretation and Coordination Features

There are some features in the application with utility irrespective of the source(s) of interest. These include person-power coordination, notification, and analyses. Here we describe the **SkyPortal** infrastructure built to address such components of the MMA workflow.

3.5.1. Shift Scheduling

The scheduling of person-power is essential to implementing a robust multi-messenger or time-domain astronomy campaign; time is of the essence when it comes to triggering the follow-up of a source or planning the observations necessary to cover the localization of an event. Within **SkyPortal**, we have introduced the concept of “shifts,” whereby each day is divided into shorter periods—usually in 4 periods of 6 hours—where teams of follow-up advocates and “shifter,” whose time zone best accommodates such a period, are assigned.

A page dedicated to the shifts has been added to **SkyPortal** to allow the creation, visualization, and management of shifts through a Google calendar-like page. On the shift calendar, one can: create a shift, join or leave a shift, delete a shift, comment on a shift, and add or remove people (for those who have the admin role). Each shift has an associated group and max shifter capacity. If said capacity is not reached within 48 hr before the start of the shift, this will be indicated on the calendar, and members of the group will be notified as




Figure 6. Shifts Page: users can see the shifts on a calendar and click on them to display more information and interact with them, as well as create new shifts.

well. Moreover, our experience during the previous O3 campaign showed us that the planning of a shifter could change at the last minute, preventing them from covering their shift and breaking the continuous monitoring of new events. To solve this problem, a feature allowing a shifter to request a replacement from other members of their group by notifying them was added. When selecting a shift on the calendar, one can see the shift management panel, the comments panel, the reminders panel, as well as the shift summary panel at the bottom of the page. On the shift summary element, a list of events that occurred during the selected shift—if any—will appear. By clicking on an event, one can see the list of sources contained within the latest localization of the event. The sources listed are the ones that have been first and last observed within one week after the first detection of the event. When leaving a comment associated with a shift in its comment section, one can mention/tag events, sources, and other users. This feature allows us to centralize and gather the work of shifters on **SkyPortal** in real-time while associating their messages with objects and events. This capability has replaced some need for collaborations to rely on external tools such as Slack, which has been the option of choice so far for this type of scheduling process.

3.5.2. Notification framework

As previously mentioned, we rely on notifications to keep users informed about recent activities within the app in a user-tunable fashion, given that not all users need to be notified of the same activities. To accomplish user-defined notifications, we built a notification framework on **SkyPortal**, where each user can specify their needs on the user profile page. On this page, one can choose to be notified of the following:

- When a given classification is added to any source, based on a list of classifications the user is interested in.
- When sources tagged as “favorites” record different activities selected by the user, such as new comments, new spectra, and new classifications.
- When a new GCN event or new GCN notice for an event already in the platform is ingested. The user can select which GCN notice types they want to be notified for, as well as specify properties of either the event itself (e.g., classification as a binary neutron star) or the skymap (e.g., size of the localization region).
- When a new facility transaction is added, including follow-up requests and observation plans.

Figure 7. User profile - Notification preferences: users can activate or deactivate notifications, specify parameters on which to notify, as well as choose where to be notified by clicking the bell icon next to each notification type.

- When a user is mentioned by another user in a comment.

For each of these notification types, in addition to the in-app notifications, the user can choose to be notified by email, Slack, SMS, WhatsApp, and/or phone call. By email and Slack, a user will always be notified. When the SMS, Whatsapp, and/or phone call option is selected, users must choose if they want to be notified while on shift, and/or every day but during a specific time period (i.e., from 8 AM to 10 PM local time). For instance, during a recent observation campaign, shifters activated notifications for new events of the notice types that the campaign was interested in (in that case, Swift notifications specifically). Moreover, the possibility of “bot” notifications to create alert channels on Slack was added; these work through the user providing a slack channel URL to interact with as a webhook. We also automatically subscribe some users to receive certain critical notifications; for instance, **SkyPortal** always notifies the admins of an allocation when a new facility transaction has been created on the instrument they are admins for. This is done to ensure that new follow-up requests or observation plan submissions cannot be missed by those responsible to trigger the associated observations on their telescopes.

3.5.3. Analysis Platform

A common way to characterize transients in optical astronomy is through the analysis of photometric, multi-band light curves. A variety of Bayesian inference frameworks have sprung up to meet the needs of transient

characterization, including MOSFiT (Guillochon et al. 2018), the “Nuclear Physics - Multi-messenger Astronomy” (NMMA) framework (Pang et al. 2022), amongst others. These frameworks are used to calculate Bayes factors for the purpose of model comparison as well as posteriors for transient characterization. While time-of-discovery analyses can reside within the purview of brokers, analysis of follow-up photometry and spectra can provide critical insights.




Figure 8. Analysis posterior for a fit to ZTF 22abykafh with the Type Ia supernova analysis service.

SkyPortal now enables a wide range of analyses on individual sources, viewing analysis packages as standalone web services capable of receiving source data and returning analysis summaries (in JSON format), parameter posteriors (in `xarray arviz.InferenceData` format; Fig. 8), and/or diagnostic plots. Site administrators first create analysis services, by providing a URL (and authentication credentials) to an existing service, the schema of required and optional parameters, and data types to be sent from **SkyPortal** to the analysis service. When an analysis is initiated (either via the front end or via API), all data viewable by the user in the analysis data types are packaged and sent to the analy-




Figure 9. Source page visualization of the AI-generated summary of using the ChatGPT 3.5 completion service on ZTF21abqhkjd (Yao et al. 2021).

sis service. Via a unique unauthenticated webhook, the analysis service then asynchronously returns analysis results. (Analysis results generated without *SkyPortal*-packaged source data and without a webhook can also be saved by an authenticated token.) The results are stored in a persistent datastore by *SkyPortal* and can be retrieved by analysis id or by querying for analysis results by source name. Posterior corner plots and other returned plots are also rendered on individual analysis pages.

While the analysis platform enables remote 3rd party services, *SkyPortal* also ships with pre-built analysis services that are run locally as microservices. A supernova service wraps the *sncosmo* (Barbary et al. 2016) fitter and an afterglow/kilonova service wraps the *numa* (Pang et al. 2022) fitter.

3.5.4. AI Summarization & Embeddings

One challenge for end-users in the face of hundreds (or thousands) of active events is maintaining a current understanding of the state of knowledge and activity for each event. To facilitate “quicklook” insights into sources, following the emergence and general availability of highly capable large language models (LLMs), the *SkyPortal* team released a pre-built analysis service to provide human-readable summaries of individual sources, using redshift, classifications, and comments. When such an analysis is initiated on a source, the summarization service formats available source data along with a predefined prompt requesting a summary; the OpenAI API (`openai.ChatCompletion`) returns a summary which is then displayed on the source (fig. 9). This summary can be easily edited, with the summary history being saved. A sitewide API key to OpenAI can be used or individual users can configure their own key and specific completion parameters. *SkyPortal* defaults to use the `gpt-3.5-turbo` model but users can opt to employ the more capable (but currently slower) `gpt-4` model.

Once a summary is created, an OpenAI embeddings service (using the `text-embedding-ada-002` model) is called with the summary that returns a vector embedding of the source in $n = 1536$ dimensions. These em-

beddings are saved in a *pinecone* database. Using these embeddings, similar sources can be retrieved by rank-ordering cosine distance metrics or natural-language queries (first embedded, then compared against the summary corpus) can be answered. Future embeddings will incorporate photometry, spectra, and annotations to further facilitate AI-guided exploration of *SkyPortal* datasets.

4. SCIENCE VALIDATION AND FIRST RESULTS

As a first demonstration of the utility of the platform, we perform an “offline” search for γ -ray burst afterglows from Fermi-GBM with ZTF. ZTF has employed an ongoing program to search for γ -ray bursts (Coughlin et al. 2019b; Ahumada et al. 2021, 2022) and gravitational waves (Coughlin et al. 2019a; Anand et al. 2020) using “triggered” Target of Opportunity (ToO) observations, which use timing and/or localization information from other wavelengths or messengers. It is similarly possible to use “serendipitous” observations akin to those performed within routine survey observations, which have neither localization nor explosion time information, to find counterparts as well (Andreoni et al. 2020b; Ho et al. 2020; Andreoni et al. 2021).

We use the short duration GRB 200826A (Ahumada et al. 2021) to recreate the offline analysis of afterglows. For this, we download the Fermi XML VO-Event files and post them to *fritz*. Later, we trigger a customized query to post candidates within the days following an event to *fritz*. The spatial cross-match employed within PostgreSQL (sec. 3.2.2) is used to keep candidates within the localization region. Limiting our queries to extragalactic fast transients, we keep transients at high Galactic latitude ($|b_{\text{Gal}}| > 10$ deg) with a fading rate faster than 0.3 mag day^{-1} in at least one band (Andreoni et al. 2021). The results of our query are displayed in the localization map, showing ZTF20abwysq among the sources recovered.

The first real-time ToO search using *fritz* was in November of 2022. We observed the localization region of the long GRB 221110A (trigger 689784662) detected by the Gamma-Ray Burst Monitor (GBM) on the Fermi satellite with ZTF. We obtained a series of g - and r -band images covering 470 square degrees beginning at 09:47 UT on 2022 Nov. 11 (~ 15 hr after the burst trigger time). This corresponded to $\sim 62\%$ of the probability enclosed in the Earth-occultation corrected GRB localization map. Each exposure was 240 sec, reaching g - and r -band median depths of 21.2 mag and 21.1 mag respectively. The images were processed in real-time through the ZTF reduction and image subtraction pipelines at IPAC (Masci et al. 2019).




Figure 10. Analysis section from the GCN event page of GRB 221110A. The GBM region is uploaded after correcting for Earth occultation, which produces a cut on the shape of the original map. The sources detected in the region covered by ZTF are shown as red dots, with their names. The *Sources* menu allows for in-depth scanning of the candidates, showing cutouts of ZTF, and other surveys, as well as the photometry of the candidate. For this event, all the sources were unrelated to the GRB.

We queried the ZTF alert stream using Kowalski (Duev et al. 2021) and AMPEL Nordin et al. (2019). We required at least 2 detections separated by at least 15 minutes to select against moving objects. The candidates within the 95% probability contour of the GRB localization map discovered for the first time after the GRB trigger time, and that have more than 2 detections are displayed in Fig. 10.

Further analysis consists of cross-matching our candidates with the Minor Planet Center to flag known asteroids, reject stellar sources (Tachibana & Miller 2018), and apply machine learning algorithms (Mahabal et al. 2019). These selection criteria as well as human vetting left us only with one candidate: ZTF22abtfyhi/AT2022aaaa. This transient was discovered at $g = 20.0$ mag, but later found to be rising (and therefore uninteresting) after SEDM optical follow-up.

Reperforming this check across a variety of serendipitous observations of γ -ray burst skymaps yields candidate quantities shown in Fig. 11.

5. DEVELOPMENT ETHOS AND CONCLUSIONS

In this paper, we have described the current state of multi-messenger functionalities within *SkyPortal* and potential future functionality. The rapid approach of O4 will provide an opportunity to identify additional




Figure 11. Scatter plot of sky area in square degrees vs. number of candidates (with at least 2 detections). The colors correspond to probability.

needs for enabling these tools to allow near-automated identification, follow-up, and characterization of potential counterparts. As an easily extensible framework, we plan a variety of improvements to the application; for example, we plan to be the first adopter of M4OPT, the Multi-Mission Multi-Messenger Observation Plan-

ning Toolkit package²¹, which is inspired by a previously prototyped Integer Linear Programming (ILP) based schedule for ZTF (Parazin et al. 2022).

We have described herein a number of frontend-focused workflows, recognizing that science in the MMA era, while greatly enhanced by software and analysis tools, remains fundamentally a collective human endeavor. Recognizing that many workflows also happen programmatically outside of **SkyPortal** the major functionality also is accessible via a well-documented API infrastructure²². It will come as no surprise that working across teams in different institutions—sometimes with aligned and sometimes with competing incentives—requires modern frameworks like **SkyPortal** to enable the establishment and curation of strict data access controls. Every photometry, spectroscopy, comment, annotation, classification entry in **SkyPortal** is permissioned by group.

SkyPortal is, first and foremost, scientific software developed to enable astronomical data science. However, a close secondary goal is to train students in proper software development practices, which has been identified as a gap between coursework and eventual readiness for academic and industry practice (Licorish et al. 2022). These required skills include software engineering skills (e.g., identifying requirements, prototyping, designing, and using version control) as well as transferable and soft skills (e.g., teamwork, and communication).

SkyPortal has had significant contributions from students at a variety of levels, with the faculty / permanent researchers associated with the project focused on bringing in students into the fold. For example, two sets of ten students from the Leonard de Vinci Engineering School have participated in the development of the features, focusing on the **icare** version of the application. This particular effort has yielded multiple internships at member institutions for these students.

However, bringing on students continues to raise a number of challenges for a small project like **SkyPortal**. First of all, the onboarding efforts for an application the size of **SkyPortal** can be challenging. For this reason, the documentation is focused on both starting the application, making basic changes, and then an example of creating a pull request is quite thorough and continues to be updated as students join the project. However, significant dedicated senior developer time is still required not only initially during the onboarding process as well as later on as the students have become comfortable

contributing; domain knowledge and project scope, as well as addressing user requests, still require significant input. This is potentially problematic given that these academic projects are led by professors with many other demands on their time.

Additionally, the international nature of this project puts an added strain on these dynamics. In addition to natural challenges with language barriers, finding times when the entire team can meet is very challenging, and in practice, multiple meetings per week with limited overlaps in persons due to time zone differences creates some challenges with ensuring a cohesive project direction.

This is further challenged by active interactions with users, which occurs in a variety of venues; as for any project, features and bug fixes are done in conjunction with user requests, which are important for sustaining both the health of the application (for reporting bugs that are not caught in the Unit Testing) as well as needed features. These user interactions occur in a variety of ways, including through a mix of Announcements through GitHub discussions, e-mail updates, Google forms, Slack and other means of communication. This level of flexibility is convenient for users, but can be challenging for developers to track feedback in a variety of forms, not only the form the communication takes but also the level of feedback (i.e. small bug fixes vs. large feature requests).

In this way, **SkyPortal** can serve as an important scientific platform for this new era of multi-messenger astronomy. We expect that software platforms of this type will become prevalent to meet the needs of the scientific user community. We expect many projects will face similar challenges as their user communities grow and students contribute; we hope that the introduction of these projects for students and others will continue to serve as important opportunities to do science while also learning best practices in a technical environment.

²¹ <https://github.com/m4opt/m4opt>

²² <https://skyportal.io/docs/api.html>

1 MWC, JL, and VS are supported by the National
 2 Science Foundation with grant number OAC-2117997;
 3 MWC is also supported by PHY-2010970. MWC and
 4 RWK were supported by the Preparing for Astrophysics
 5 with LSST Program, funded by the Heising Simons
 6 Foundation through grant 2021-2975, and administered
 7 by Las Cumbres Observatory. The Gordon and Betty
 8 Moore Foundation, through both the Data-Driven In-
 9 vestigator Program and a dedicated grant to develop
 10 SkyPortal, provided critical funding for this project
 11 without which this project could not have succeeded.
 12 J.S.B., G.N., A.C-Q., D.A.D. were partially supported
 13 by the Gordon and Betty Moore Foundation. BP
 14 thanks the Northeastern Lawrence Co-op Fellowship
 15 for their continuous support. JP thanks LSST-France
 16 and CNRS/IN2P3 for supporting Fink. The Kilonova-
 17 Catcher program is supported by the IdEx Université
 18 de Paris Cité, ANR-18-IDEX-0001 and the MITI CNRS
 19 Sciences participative program.

20 Based on observations obtained with the Samuel
 21 Oschin Telescope 48-inch and the 60-inch Telescope at
 22 the Palomar Observatory as part of the Zwicky Tran-
 23 sient Facility project. ZTF is supported by the National
 24 Science Foundation under Grant No. AST-2034437 and
 25 a collaboration including Caltech, IPAC, the Weizmann
 26 Institute of Science, the Oskar Klein Center at Stock-
 27 holm University, the University of Maryland, Deutsches
 28 Elektronen-Synchrotron and Humboldt University, the
 29 TANGO Consortium of Taiwan, the University of Wis-
 30 consin at Milwaukee, Trinity College Dublin, Lawrence
 31 Livermore National Laboratories, IN2P3, University of
 32 Warwick, Ruhr University Bochum and Northwestern
 33 University. Operations are conducted by COO, IPAC,
 34 and UW.

REFERENCES

- Aartsen, M., Ackermann, M., Adams, J., et al. 2017, *Journal of Instrumentation*, 12, P03012, doi: [10.1088/1748-0221/12/03/p03012](https://doi.org/10.1088/1748-0221/12/03/p03012)
- Aasi et al. 2015, *Classical and Quantum Gravity*, 32, 074001
- Abbott, B. P., Abbott, R., Abbott, T. D., et al. 2017, *Nature*, 551, 85, doi: [10.1038/nature24471](https://doi.org/10.1038/nature24471)
- Abbott et al. 2017a, *Phys. Rev. Lett.*, 119, 161101, doi: [10.1103/PhysRevLett.119.161101](https://doi.org/10.1103/PhysRevLett.119.161101)
- . 2017b, *The Astrophysical Journal Letters*, 848, L12. <http://stacks.iop.org/2041-8205/848/i=2/a=L12>
- . 2017c, *The Astrophysical Journal Letters*, 848, L13. <http://stacks.iop.org/2041-8205/848/i=2/a=L13>
- Acernese et al. 2015, *Classical and Quantum Gravity*, 32, 024001
- Ackley, K., Amati, L., Barbieri, C., et al. 2020, *A&A*, 643, A113, doi: [10.1051/0004-6361/202037669](https://doi.org/10.1051/0004-6361/202037669)
- Ahumada, T., Singer, L. P., Anand, S., et al. 2021, *Nature Astronomy*, 5, 917, doi: [10.1038/s41550-021-01428-7](https://doi.org/10.1038/s41550-021-01428-7)
- Ahumada, T., Anand, S., Coughlin, M. W., et al. 2022, *The Astrophysical Journal*, 932, 40, doi: [10.3847/1538-4357/ac6c29](https://doi.org/10.3847/1538-4357/ac6c29)
- Aivazyan, V., Almualla, M., Antier, S., et al. 2022, *Monthly Notices of the Royal Astronomical Society*, 515, 6007, doi: [10.1093/mnras/stac2054](https://doi.org/10.1093/mnras/stac2054)

- Allan, A., Denny, R. B., & Swinbank, J. D. 2017, arXiv preprint arXiv:1709.01264
- Almualla, M., Coughlin, M. W., Anand, S., et al. 2020, *Mon. Not. R. Astron. Soc.*, 495, 4366, doi: [10.1093/mnras/staa1498](https://doi.org/10.1093/mnras/staa1498)
- Anand, S., Coughlin, M. W., Kasliwal, M. M., et al. 2020, *Nature Astronomy*, doi: [10.1038/s41550-020-1183-3](https://doi.org/10.1038/s41550-020-1183-3)
- Andreoni, I., Goldstein, D. A., Anand, S., et al. 2019, *ApJL*, 881, L16, doi: [10.3847/2041-8213/ab3399](https://doi.org/10.3847/2041-8213/ab3399)
- Andreoni, I., Goldstein, D. A., Kasliwal, M. M., et al. 2020a, *ApJ*, 890, 131, doi: [10.3847/1538-4357/ab6a1b](https://doi.org/10.3847/1538-4357/ab6a1b)
- Andreoni, I., Kool, E. C., Sagués Carracedo, A., et al. 2020b, *ApJ*, 904, 155, doi: [10.3847/1538-4357/abbf4c](https://doi.org/10.3847/1538-4357/abbf4c)
- Andreoni, I., Coughlin, M. W., Kool, E. C., et al. 2021, *The Astrophysical Journal*, 918, 63, doi: [10.3847/1538-4357/ac0bc7](https://doi.org/10.3847/1538-4357/ac0bc7)
- Antier, S., Agayeva, S., Aivazyan, V., et al. 2019, *Monthly Notices of the Royal Astronomical Society*, 492, 3904, doi: [10.1093/mnras/stz3142](https://doi.org/10.1093/mnras/stz3142)
- Antier, S., Agayeva, S., Almualla, M., et al. 2020, *Monthly Notices of the Royal Astronomical Society*, 497, 5518, doi: [10.1093/mnras/staa1846](https://doi.org/10.1093/mnras/staa1846)
- Arcavi, I., Hosseinzadeh, G., Howell, D. A., et al. 2017, *Nature*, 551, 64, doi: [10.1038/nature24291](https://doi.org/10.1038/nature24291)
- Barbary, K., Barclay, T., Biswas, R., et al. 2016, *SNCosmo*: Python library for supernova cosmology. <http://ascl.net/1611.017>
- Barthelmy, S. D., Butterworth, P., Cline, T. L., et al. 1995, *Astrophysics and Space Science*, 231, 235
- Bellm, E. C., Kulkarni, S. R., Barlow, T., et al. 2019, *PASP*, 131, 068003
- Biswas, B., Ishida, E. E. O., Peloton, J., et al. 2022. <https://arxiv.org/abs/2210.17433>
- Blagorodnova, N., Neill, J. D., Walters, R., et al. 2018, *Publications of the Astronomical Society of the Pacific*, 130, 035003. <http://stacks.iop.org/1538-3873/130/i=985/a=035003>
- Bokeh Development Team. 2018, *Bokeh*: Python library for interactive visualization. <https://bokeh.pydata.org/en/latest/>
- Bulla, M. 2019, *MNRAS*, 489, 5037, doi: [10.1093/mnras/stz2495](https://doi.org/10.1093/mnras/stz2495)
- . 2023, *MNRAS*, 520, 2558, doi: [10.1093/mnras/stad232](https://doi.org/10.1093/mnras/stad232)
- Chambers, K. C., Magnier, E. A., Metcalfe, N., et al. 2016, arXiv e-prints, arXiv:1612.05560. <https://arxiv.org/abs/1612.05560>
- Chornock et al. 2017, *The Astrophysical Journal Letters*, 848, L19. <http://stacks.iop.org/2041-8205/848/i=2/a=L19>
- Cook, D. O., Kasliwal, M. M., Van Sistine, A., et al. 2017, ArXiv e-prints. <https://arxiv.org/abs/1710.05016>
- Coughlin, M. W. 2020, *Nature Astronomy*, 4, 550, doi: [10.1038/s41550-020-1130-3](https://doi.org/10.1038/s41550-020-1130-3)
- Coughlin, M. W., Tao, D., Chan, M. L., et al. 2018, *Monthly Notices of the Royal Astronomical Society*, 478, 692, doi: [10.1093/mnras/sty1066](https://doi.org/10.1093/mnras/sty1066)
- Coughlin, M. W., Ahumada, T., Anand, S., et al. 2019a, *The Astrophysical Journal*, 885, L19, doi: [10.3847/2041-8213/ab4ad8](https://doi.org/10.3847/2041-8213/ab4ad8)
- Coughlin, M. W., Ahumada, T., Cenko, S. B., et al. 2019b, *Publications of the Astronomical Society of the Pacific*, 131, 048001, doi: [10.1088/1538-3873/aaff99](https://doi.org/10.1088/1538-3873/aaff99)
- Coughlin, M. W., Antier, S., Corre, D., et al. 2019c, *Monthly Notices of the Royal Astronomical Society*, doi: [10.1093/mnras/stz2485](https://doi.org/10.1093/mnras/stz2485)
- Coughlin, M. W., Dietrich, T., Antier, S., et al. 2019d, *Monthly Notices of the Royal Astronomical Society*, 492, 863, doi: [10.1093/mnras/stz3457](https://doi.org/10.1093/mnras/stz3457)
- Coughlin, M. W., Dietrich, T., Heinzel, J., et al. 2020a, *Phys. Rev. Research*, 2, 022006, doi: [10.1103/PhysRevResearch.2.022006](https://doi.org/10.1103/PhysRevResearch.2.022006)
- Coughlin, M. W., Antier, S., Dietrich, T., et al. 2020b, *Nature Communications*, 11, 4129, doi: [10.1038/s41467-020-17998-5](https://doi.org/10.1038/s41467-020-17998-5)
- Coughlin, M. W., Dietrich, T., Antier, S., et al. 2020c, *Monthly Notices of the Royal Astronomical Society*, 497, 1181–1196, doi: [10.1093/mnras/staa1925](https://doi.org/10.1093/mnras/staa1925)
- Coughlin, M. W., Burdge, K., Duev, D. A., et al. 2021, *Monthly Notices of the Royal Astronomical Society*, 505, 2954–2965, doi: [10.1093/mnras/stab1502](https://doi.org/10.1093/mnras/stab1502)
- Coulter, D. A., Foley, R. J., Kilpatrick, C. D., et al. 2017, *Science*, 358, 1556, doi: [10.1126/science.aap9811](https://doi.org/10.1126/science.aap9811)
- Coulter, D. A., Jones, D. O., McGill, P., et al. 2023, arXiv e-prints, arXiv:2303.02154. <https://arxiv.org/abs/2303.02154>
- Coulter et al. 2017, *Science*, 358, 1556, doi: [10.1126/science.aap9811](https://doi.org/10.1126/science.aap9811)
- Cowperthwaite, P. S., Berger, E., Villar, V. A., et al. 2017, *ApJL*, 848, L17, doi: [10.3847/2041-8213/aa8fc7](https://doi.org/10.3847/2041-8213/aa8fc7)
- Cutri, R. M., & et al. 2012, *VizieR Online Data Catalog*, II/311
- Cutri, R. M., Skrutskie, M. F., van Dyk, S., et al. 2003, *2MASS All Sky Catalog of point sources*.
- Dalya, G., Diaz, R., Bouchet, F., et al. 2021, *VizieR Online Data Catalog*, VII
- De, K., Hankins, M. J., Kasliwal, M. M., et al. 2020, *PASP*, 132, 025001, doi: [10.1088/1538-3873/ab6069](https://doi.org/10.1088/1538-3873/ab6069)

- Dekany, R., Smith, R. M., Riddle, R., et al. 2020, Publications of the Astronomical Society of the Pacific, 132, 038001, doi: [10.1088/1538-3873/ab4ca2](https://doi.org/10.1088/1538-3873/ab4ca2)
- Dietrich, T., Coughlin, M. W., Pang, P. T. H., et al. 2020, Science, 370, 1450, doi: [10.1126/science.abb4317](https://doi.org/10.1126/science.abb4317)
- Duev, D. A., Mahabal, A., Masci, F. J., et al. 2019, Monthly Notices of the Royal Astronomical Society, 489, 3582–3590, doi: [10.1093/mnras/stz2357](https://doi.org/10.1093/mnras/stz2357)
- Duev, D. A., Bolin, B. T., Graham, M. J., et al. 2021, The Astronomical Journal, 161, 218, doi: [10.3847/1538-3881/abea7b](https://doi.org/10.3847/1538-3881/abea7b)
- Feinadt, U., Nordin, J., Rigault, M., et al. 2019, Journal of Cosmology and Astroparticle Physics, 2019, 005–005, doi: [10.1088/1475-7516/2019/10/005](https://doi.org/10.1088/1475-7516/2019/10/005)
- Fernique, P., Boch, T., Donaldson, T., et al. 2014, MOC - HEALPix Multi-Order Coverage map Version 1.0, IVOA Recommendation 02 June 2014. <https://arxiv.org/abs/1505.02937>
- Fernique, P., Boch, T., Donaldson, T., et al. 2015, arXiv preprint arXiv:1505.02937
- Fernique, P., Nebot, A., Durand, D., et al. 2022, IVOA Recommendation 27 July 2022, 727
- Flewelling, H. 2018, in American Astronomical Society Meeting Abstracts, Vol. 231, American Astronomical Society Meeting Abstracts #231, 436.01
- Fremling, C., Miller, A. A., Sharma, Y., et al. 2020, The Zwicky Transient Facility Bright Transient Survey. I. Spectroscopic Classification and the Redshift Completeness of Local Galaxy Catalogs, doi: [10.3847/1538-4357/ab8943](https://doi.org/10.3847/1538-4357/ab8943)
- Fremling, C., Hall, X. J., Coughlin, M. W., et al. 2021, The Astrophysical Journal Letters, 917, L2, doi: [10.3847/2041-8213/ac116f](https://doi.org/10.3847/2041-8213/ac116f)
- Förster, F., Cabrera-Vives, G., Castillo-Navarrete, E., et al. 2021, The Astronomical Journal, 161, 242, doi: [10.3847/1538-3881/abe9bc](https://doi.org/10.3847/1538-3881/abe9bc)
- Gehrels et al. 2004, ApJ, 611, 1005, doi: [10.1086/422091](https://doi.org/10.1086/422091)
- Goldstein, A., Veres, P., Burns, E., et al. 2017, The Astrophysical Journal, 848, L14, doi: [10.3847/2041-8213/aa8f41](https://doi.org/10.3847/2041-8213/aa8f41)
- Goldstein, D. A., Andreoni, I., Nugent, P. E., et al. 2019, ApJL, 881, L7, doi: [10.3847/2041-8213/ab3046](https://doi.org/10.3847/2041-8213/ab3046)
- Gomez, S., Hosseinzadeh, G., Cowperthwaite, P. S., et al. 2019, ApJL, 884, L55, doi: [10.3847/2041-8213/ab4ad5](https://doi.org/10.3847/2041-8213/ab4ad5)
- Gompertz, B. P., Cutter, R., Steeghs, D., et al. 2020, Monthly Notices of the Royal Astronomical Society, 497, 726–738, doi: [10.1093/mnras/staa1845](https://doi.org/10.1093/mnras/staa1845)
- Górski, K. M., Hivon, E., Banday, A. J., et al. 2005, ApJ, 622, 759, doi: [10.1086/427976](https://doi.org/10.1086/427976)
- Graham, M. J., Kulkarni, S. R., Bellm, E. C., et al. 2019, Publications of the Astronomical Society of the Pacific, 131, 078001, doi: [10.1088/1538-3873/ab006c](https://doi.org/10.1088/1538-3873/ab006c)
- Guillochon, J., Nicholl, M., Villar, V. A., et al. 2018, The Astrophysical Journal Supplement Series, 236, 6, doi: [10.3847/1538-4365/aab761](https://doi.org/10.3847/1538-4365/aab761)
- Ho, A. Y. Q., Perley, D. A., Beniamini, P., et al. 2020, ApJ, 905, 98, doi: [10.3847/1538-4357/abc34d](https://doi.org/10.3847/1538-4357/abc34d)
- Hotokezaka, K., Nakar, E., Gottlieb, O., et al. 2019, Nature Astronomy, 3, 940, doi: [10.1038/s41550-019-0820-1](https://doi.org/10.1038/s41550-019-0820-1)
- Ivezić, Ž., Kahn, S. M., Tyson, J. A., et al. 2019, ApJ, 873, 111, doi: [10.3847/1538-4357/ab042c](https://doi.org/10.3847/1538-4357/ab042c)
- Kasliwal, M. M., Kasen, D., Lau, R. M., et al. 2019, Monthly Notices of the Royal Astronomical Society: Letters, doi: [10.1093/mnrasl/slz007](https://doi.org/10.1093/mnrasl/slz007)
- Kasliwal, M. M., Anand, S., Ahumada, T., et al. 2020, ApJ, 905, 145, doi: [10.3847/1538-4357/abc335](https://doi.org/10.3847/1538-4357/abc335)
- Li, W., Filippenko, A. V., Chornock, R., & Jha, S. 2003, Publications of the Astronomical Society of the Pacific, 115, 844, doi: [10.1086/376432](https://doi.org/10.1086/376432)
- Licorish, S. A., Galster, M., Kapitsaki, G. M., & Tahir, A. 2022, Journal of Systems and Software, 186, 111156, doi: <https://doi.org/10.1016/j.jss.2021.111156>
- Lourie, N. P., Baker, J. W., Burruss, R. S., et al. 2020, in Society of Photo-Optical Instrumentation Engineers (SPIE) Conference Series, Vol. 11447, Society of Photo-Optical Instrumentation Engineers (SPIE) Conference Series, 114479K, doi: [10.1117/12.2561210](https://doi.org/10.1117/12.2561210)
- Lourie, N. P., Baker, J. W., Burruss, R. S., et al. 2020, in Ground-based and Airborne Instrumentation for Astronomy VIII, ed. C. J. Evans, J. J. Bryant, & K. Motohara (SPIE), doi: [10.1117/12.2561210](https://doi.org/10.1117/12.2561210)
- Lundquist, M. J., Paterson, K., Fong, W., et al. 2019, The Astrophysical Journal, 881, L26, doi: [10.3847/2041-8213/ab32f2](https://doi.org/10.3847/2041-8213/ab32f2)
- Mahabal, A., Rebbapragada, U., Walters, R., et al. 2019, Publications of the Astronomical Society of the Pacific, 131, 038002, doi: [10.1088/1538-3873/aaf3fa](https://doi.org/10.1088/1538-3873/aaf3fa)
- Masci, F. J., Laher, R. R., Rusholme, B., et al. 2019, PASP, 131, 018003, doi: [10.1088/1538-3873/aae8ac](https://doi.org/10.1088/1538-3873/aae8ac)
- Matheson, T., Stubens, C., Wolf, N., et al. 2021, The Astronomical Journal, 161, 107, doi: [10.3847/1538-3881/abd703](https://doi.org/10.3847/1538-3881/abd703)
- Meegan et al. 2009, The Astrophysical Journal, 702, 791. <http://stacks.iop.org/0004-637X/702/i=1/a=791>
- Metzger, B. D. 2017, Living Rev. Rel., 20, 3, doi: [10.1007/s41114-017-0006-z](https://doi.org/10.1007/s41114-017-0006-z)
- Möller, A., Peloton, J., Ishida, E. E. O., et al. 2020, Monthly Notices of the Royal Astronomical Society, 501, 3272, doi: [10.1093/mnras/staa3602](https://doi.org/10.1093/mnras/staa3602)

- Naul, B., van der Walt, S., Crellin-Quick, A., Bloom, J. S., & Pérez, F. 2016, Proceedings of the 15th Python in Science Conference (SciPy 2016), arXiv:1609.04504, doi: [10.48550/arXiv.1609.04504](https://doi.org/10.48550/arXiv.1609.04504)
- Nordin, J., Brinnel, V., van Santen, J., et al. 2019, *A&A*, 631, A147, doi: [10.1051/0004-6361/201935634](https://doi.org/10.1051/0004-6361/201935634)
- Pang, P. T. H., Dietrich, T., Coughlin, M. W., et al. 2022, NMMA: A nuclear-physics and multi-messenger astrophysics framework to analyze binary neutron star mergers, arXiv, doi: [10.48550/ARXIV.2205.08513](https://doi.org/10.48550/ARXIV.2205.08513)
- Parazin, B., Coughlin, M. W., Singer, L. P., Gupta, V., & Anand, S. 2022, *The Astrophysical Journal*, 935, 87, doi: [10.3847/1538-4357/ac7fa2](https://doi.org/10.3847/1538-4357/ac7fa2)
- Patterson, M. T., Bellm, E. C., Rusholme, B., et al. 2018, *Publications of the Astronomical Society of the Pacific*, 131, 018001, doi: [10.1088/1538-3873/aae904](https://doi.org/10.1088/1538-3873/aae904)
- Perley, D. A., Fremling, C., Sollerman, J., et al. 2020, *ApJ*, 904, 35, doi: [10.3847/1538-4357/abbd98](https://doi.org/10.3847/1538-4357/abbd98)
- Petrov, P., Singer, L. P., Coughlin, M. W., et al. 2022, *The Astrophysical Journal*, 924, 54, doi: [10.3847/1538-4357/ac366d](https://doi.org/10.3847/1538-4357/ac366d)
- Pian et al. 2017, *Nature*, 551, 67 EP . <http://dx.doi.org/10.1038/nature24298>
- Ricker, G. R., Winn, J. N., Vanderspek, R., et al. 2014, in *Society of Photo-Optical Instrumentation Engineers (SPIE) Conference Series*, Vol. 9143, Proc. SPIE, 914320, doi: [10.1117/12.2063489](https://doi.org/10.1117/12.2063489)
- Rigault, M., Neill, J. D., Blagorodnova, N., et al. 2019, *A&A*, 627, A115, doi: [10.1051/0004-6361/201935344](https://doi.org/10.1051/0004-6361/201935344)
- Rosswog, S., Feindt, U., Korobkin, O., et al. 2017, *Class. Quant. Grav.*, 34, 104001, doi: [10.1088/1361-6382/aa68a9](https://doi.org/10.1088/1361-6382/aa68a9)
- Rosswog, S., Sollerman, J., Feindt, U., et al. 2018, *A&A*, 615, A132, doi: [10.1051/0004-6361/201732117](https://doi.org/10.1051/0004-6361/201732117)
- Ryan, G., Eerten, H. v., Piro, L., & Troja, E. 2020, *The Astrophysical Journal*, 896, 166, doi: [10.3847/1538-4357/ab93cf](https://doi.org/10.3847/1538-4357/ab93cf)
- Savchenko, V., Ferrigno, C., Kuulkers, E., et al. 2017, *The Astrophysical Journal*, 848, L15, doi: [10.3847/2041-8213/aa8f94](https://doi.org/10.3847/2041-8213/aa8f94)
- Schüssler, F., Alkan, A. K., Lefranc, V., & Reichherzer, P. 2021, in *Proceedings of 37th International Cosmic Ray Conference — PoS(ICRC2021)* (Sissa Medialab), doi: [10.22323/1.395.0935](https://doi.org/10.22323/1.395.0935)
- Seaman, R., Williams, R., Allan, A., et al. 2011, *Sky Event Reporting Metadata Version 2.0, IVOA Recommendation* 11 July 2011, doi: [10.5479/ADS/bib/2011ivoa.spec.0711S](https://doi.org/10.5479/ADS/bib/2011ivoa.spec.0711S)
- Singer, L., & Racusin, J. 2023, *Bulletin of the AAS*, 55
- Singer, L. P., Parazin, B., Coughlin, M. W., et al. 2022a, *The Astronomical Journal*, 163, 209, doi: [10.3847/1538-3881/ac5ab8](https://doi.org/10.3847/1538-3881/ac5ab8)
- . 2022b, *The Astronomical Journal*, 163, 209
- Smartt et al. 2017, *Nature*, 551, 75 EP . <http://dx.doi.org/10.1038/nature24303>
- Smith, K. W., Williams, R. D., Young, D. R., et al. 2019, *Research Notes of the AAS*, 3, 26, doi: [10.3847/2515-5172/ab020f](https://doi.org/10.3847/2515-5172/ab020f)
- Smith, K. W., Smartt, S. J., Young, D. R., et al. 2020, *PASP*, 132, 085002, doi: [10.1088/1538-3873/ab936e](https://doi.org/10.1088/1538-3873/ab936e)
- Steele et al. 2004, *The Liverpool Telescope: performance and first results*, doi: [10.1117/12.551456](https://doi.org/10.1117/12.551456)
- Stonebraker, M., & Rowe, L. A. 1986, in *Proceedings of the 1986 ACM SIGMOD International Conference on Management of Data, SIGMOD '86* (New York, NY, USA: Association for Computing Machinery), 340–355, doi: [10.1145/16894.16888](https://doi.org/10.1145/16894.16888)
- Street, R. A., Bowman, M., Saunders, E. S., & Boroson, T. 2018, in *Software and Cyberinfrastructure for Astronomy V*, ed. J. C. Guzman & J. Ibsen, Vol. 10707, *International Society for Optics and Photonics (SPIE)*, 274 – 284, doi: [10.1117/12.2312293](https://doi.org/10.1117/12.2312293)
- Tachibana & Miller. 2018, *Publications of the Astronomical Society of the Pacific*, 130, 128001, doi: [10.1088/1538-3873/aae3d9](https://doi.org/10.1088/1538-3873/aae3d9)
- Tonry, J. L., Denneau, L., Heinze, A. N., et al. 2018, *Publications of the Astronomical Society of the Pacific*, 130, 064505. <http://stacks.iop.org/1538-3873/130/i=988/a=064505>
- Valenti et al. 2017, *The Astrophysical Journal Letters*, 848, L24. <http://stacks.iop.org/2041-8205/848/i=2/a=L24>
- van der Walt, S. J., Crellin-Quick, A., & Bloom, J. S. 2019, *Journal of Open Source Software*, 4, doi: [10.21105/joss.01247](https://doi.org/10.21105/joss.01247)
- van Roestel, J., Duev, D. A., Mahabal, A. A., et al. 2021, *The Astronomical Journal*, 161, 267, doi: [10.3847/1538-3881/abe853](https://doi.org/10.3847/1538-3881/abe853)
- Watson, D., Hansen, C. J., Selsing, J., et al. 2019, *Nature*, 574, 497, doi: [10.1038/s41586-019-1676-3](https://doi.org/10.1038/s41586-019-1676-3)
- Wyatt, S. D., Tohuvavohu, A., Arcavi, I., et al. 2020, *The Astrophysical Journal*, 894, 127, doi: [10.3847/1538-4357/ab855e](https://doi.org/10.3847/1538-4357/ab855e)
- Yao, Y., Gezari, S., Velzen, S. V., et al. 2021, *Transient Name Server AstroNote*, 258, 1
- Zechmeister, M., & Kürster, M. 2009, *A&A*, 496, 577, doi: [10.1051/0004-6361:200811296](https://doi.org/10.1051/0004-6361:200811296)